

OPAQUE PIGMENT GREY BARNES PRODUCTS PTY LTD

Chemwatch: 9848799 Version No: 10.1

Safety Data Sheet according to the Health and Safety at Work (Hazardous Substances) Regulations 2017

Chemwatch Hazard Alert Code: '

Issue Date: **17/03/2023** Print Date: **08/06/2023** S.GHS.NZL.EN.E

SECTION 1 Identification of the substance / mixture and of the company / undertaking

Product Identifier

1 Todate Identifier	
Product name	OPAQUE PIGMENT GREY
Chemical Name	Not Applicable
Synonyms	6835 GREY
Chemical formula	Not Applicable
Other means of identification	Not Available

Relevant identified uses of the substance or mixture and uses advised against

Relevant identified uses Pigment.

Details of the manufacturer or supplier of the safety data sheet

Registered company name	BARNES PRODUCTS PTY LTD	
Address	GREENHILLS AVE MOOREBANK NSW 2170 Australia	
Telephone	Barnes Australia +612 9793 7555 Mon-Fri 8am-4:30pm	
Fax	Barnes Australia +612 9793 7091	
Website	www.barnesnz.co.nz	
Email	sales@barnes.com.au	

Emergency telephone number

Association / Organisation	New Zealand Poisons Information Centre	
Emergency telephone numbers	Barnes NZ +649 9731 816 - Monday-Thursday 9am-5pm Friday 9am-4.30pm	
Other emergency telephone numbers	New Zealand Poisons Information Centre 0800 764 766 After Hours	

SECTION 2 Hazards identification

Classification of the substance or mixture

Classification [1]	Serious Eye Damage/Eye Irritation Category 2, Hazardous to Soil Organisms	
Legend:	. Classified by Chemwatch; 2. Classification drawn from CCID EPA NZ; 3. Classification drawn from Regulation (EU) No 1272/2008 - Annex VI	
Determined by Chemwatch using GHS/HSNO criteria	6.4A, 9.2C	

Label elements

Hazard pictogram(s)



Signal word

Warning

Hazard statement(s)

H319	Causes serious eye irritation.
H423	Hazardous to soil organisms.

Precautionary statement(s) Prevention

P280	Wear protective gloves, protective clothing, eye protection and face protection.
P264	Wash all exposed external body areas thoroughly after handling.

Chemwatch: **9848799** Page **2** of **11**

Version No: 10.1 OPAQUE PIGMENT GREY

Precautionary statement(s) Response

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P337+P313 If eye irritation persists: Get medical advice/attention.

Precautionary statement(s) Storage

Not Applicable

Precautionary statement(s) Disposal

Not Applicable

SECTION 3 Composition / information on ingredients

Substances

See section below for composition of Mixtures

Mixtures

CAS No	%[weight]	Name
13463-67-7	30-60	titanium dioxide
68515-49-1	15-40	di-C9-11-alkyl phthalate, C10-rich
1333-86-4	5-10	carbon black
21645-51-2	1-5	aluminium hydroxide
7631-86-9	1-5	silica amorphous
Legend: 1. Classified by Chemwatch; 2. Classification drawn from CCID EPA NZ; 3. Classification drawn from Regulation (EU) No 1272/2008 - Annex V 4. Classification drawn from C&L * EU IOELVs available		

SECTION 4 First aid measures

Description	of firet	hic	mageurae
Describtion	OI IIISt	aıu	measures

Eye Contact	If this product comes in contact with the eyes: Immediately hold eyelids apart and flush the eye continuously with running water. Ensure complete irrigation of the eye by keeping eyelids apart and away from eye and moving the eyelids by occasionally lifting the upper and lower lids. Continue flushing until advised to stop by the Poisons Information Centre or a doctor, or for at least 15 minutes. Transport to hospital or doctor without delay. Removal of contact lenses after an eye injury should only be undertaken by skilled personnel.
Skin Contact	If skin contact occurs: Immediately remove all contaminated clothing, including footwear. Flush skin and hair with running water (and soap if available). Seek medical attention in event of irritation.
Inhalation	 If fumes, aerosols or combustion products are inhaled remove from contaminated area. Other measures are usually unnecessary.
Ingestion	 If swallowed do NOT induce vomiting. If vomiting occurs, lean patient forward or place on left side (head-down position, if possible) to maintain open airway and prevent aspiration. Observe the patient carefully. Never give liquid to a person showing signs of being sleepy or with reduced awareness; i.e. becoming unconscious. Give water to rinse out mouth, then provide liquid slowly and as much as casualty can comfortably drink. Seek medical advice.

Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

SECTION 5 Firefighting measures

Extinguishing media

- ► Foam.
- Dry chemical powder.
- ► BCF (where regulations permit).
- Carbon dioxide.
- ▶ Water spray or fog Large fires only.

Special hazards arising from the substrate or mixture

Fire Incompatibility Avoid contamination with oxidising agents i.e. nitrates, oxidising acids, chlorine bleaches, pool chlorine etc. as ignition may result

Advice for firefighters

- Alert Fire Brigade and tell them location and nature of hazard.
- Wear breathing apparatus plus protective gloves.
- Prevent, by any means available, spillage from entering drains or water courses.
- Fire Fighting
 Use water delivered as a fine spray to control fire and cool adjacent area.
 - ▶ DO NOT approach containers suspected to be hot.
 - ▶ Cool fire exposed containers with water spray from a protected location.
 - If safe to do so, remove containers from path of fire.

Issue Date: 17/03/2023

Print Date: 08/06/2023

Chemwatch: 9848799 Page 3 of 11 Issue Date: 17/03/2023 Version No: 10.1

OPAQUE PIGMENT GREY

Print Date: 08/06/2023

- Slight fire hazard when exposed to heat or flame.
- ▶ Heating may cause expansion or decomposition leading to violent rupture of containers.
- ▶ On combustion, may emit toxic fumes of carbon monoxide (CO).
- May emit acrid smoke.
- Mists containing combustible materials may be explosive.

Combustion products include:

carbon dioxide (CO2)

Combustible

other pyrolysis products typical of burning organic material.

May emit poisonous fumes May emit corrosive fumes.

SECTION 6 Accidental release measures

Fire/Explosion Hazard

Personal precautions, protective equipment and emergency procedures

See section 8

Environmental precautions

See section 12

Methods and material for containment and cleaning up

3 -r		
Minor Spills	Environmental hazard - contain spillage. Remove all ignition sources. Clean up all spills immediately. Avoid breathing vapours and contact with skin and eyes. Control personal contact with the substance, by using protective equipment. Contain and absorb spill with sand, earth, inert material or vermiculite. Wipe up. Place in a suitable, labelled container for waste disposal.	
Major Spills	Environmental hazard - contain spillage. Moderate hazard. Clear area of personnel and move upwind. Alert Fire Brigade and tell them location and nature of hazard. Wear breathing apparatus plus protective gloves. Prevent, by any means available, spillage from entering drains or water course. No smoking, naked lights or ignition sources. Increase ventilation.	

Personal Protective Equipment advice is contained in Section 8 of the SDS.

SECTION 7 Handling and storage

Precautions for safe handling ▶ DO NOT allow clothing wet with material to stay in contact with skin

Safe handling	 Avoid all personal contact, including inhalation. Wear protective clothing when risk of exposure occurs. Use in a well-ventilated area. Prevent concentration in hollows and sumps. DO NOT enter confined spaces until atmosphere has been checked. Avoid smoking, naked lights or ignition sources. Avoid contact with incompatible materials.
	 Store in original containers. Keep containers securely sealed. No smoking, naked lights or ignition sources.

Other information

- ► Store in a cool, dry, well-ventilated area. ▶ Store away from incompatible materials and foodstuff containers.
- Protect containers against physical damage and check regularly for leaks.
- ▶ Observe manufacturer's storage and handling recommendations contained within this SDS.

Conditions for safe storage, including any incompatibilities

Suitable container	Packaging as recommended by manufacturer.	
Storage incompatibility	Avoid reaction with oxidising agents	

SECTION 8 Exposure controls / personal protection

Control parameters

Occupational Exposure Limits (OEL)

INGREDIENT DATA

MOREDIENT DATA						
Source	Ingredient	Material name	TWA	STEL	Peak	Notes
New Zealand Workplace Exposure Standards (WES)	titanium dioxide	Titanium dioxide	10 mg/m3	Not Available	Not Available	Not Available
New Zealand Workplace Exposure Standards (WES)	carbon black	Carbon black	3 mg/m3	Not Available	Not Available	carcinogen category 2 - Suspected human carcinogen
New Zealand Workplace Exposure Standards (WES)	aluminium hydroxide	Inhalable dust (not otherwise classified)	10 mg/m3	Not Available	Not Available	Not Available

Chemwatch: **9848799** Page **4** of **11**

Version No: 10.1 OPAQUE PIGMENT GREY

Print Date: 08/06/2023

Source	Ingredient	Material name	TWA	STEL	Peak	Notes
New Zealand Workplace Exposure Standards (WES)	aluminium hydroxide	Respirable dust (not otherwise classified)	3 mg/m3	Not Available	Not Available	Not Available
New Zealand Workplace Exposure Standards (WES)	silica amorphous	Silica fused respirable dust	0.2 mg/m3	Not Available	Not Available	Not Available
New Zealand Workplace Exposure Standards (WES)	silica amorphous	Precipitated silica (Silica- Amorphous)	10 mg/m3	Not Available	Not Available	Not Available
New Zealand Workplace Exposure Standards (WES)	silica amorphous	Diatomaceous earth (not calcined)	10 mg/m3	Not Available	Not Available	Not Available
New Zealand Workplace Exposure Standards (WES)	silica amorphous	Silica-Amorphous, Precipitated silica	10 mg/m3	Not Available	Not Available	Not Available
New Zealand Workplace Exposure Standards (WES)	silica amorphous	Silica fume respirable dust	3 mg/m3	Not Available	Not Available	Not Available

Emergency Limits

Ingredient	TEEL-1	TEEL-2	TEEL-3
titanium dioxide	30 mg/m3	330 mg/m3	2,000 mg/m3
carbon black	9 mg/m3	99 mg/m3	590 mg/m3
aluminium hydroxide	8.7 mg/m3	73 mg/m3	440 mg/m3
silica amorphous	18 mg/m3	200 mg/m3	1,200 mg/m3
silica amorphous	18 mg/m3	100 mg/m3	630 mg/m3
silica amorphous	120 mg/m3	1,300 mg/m3	7,900 mg/m3
silica amorphous	45 mg/m3	500 mg/m3	3,000 mg/m3
silica amorphous	18 mg/m3	740 mg/m3	4,500 mg/m3

Ingredient	Original IDLH	Revised IDLH
titanium dioxide	5,000 mg/m3	Not Available
di-C9-11-alkyl phthalate, C10-rich	Not Available	Not Available
carbon black	1,750 mg/m3	Not Available
aluminium hydroxide	Not Available	Not Available
silica amorphous	3,000 mg/m3	Not Available

Exposure controls

Appropriate engineering controls

Engineering controls are used to remove a hazard or place a barrier between the worker and the hazard. Well-designed engineering controls can be highly effective in protecting workers and will typically be independent of worker interactions to provide this high level of protection. The basic types of engineering controls are:

Process controls which involve changing the way a job activity or process is done to reduce the risk.

Enclosure and/or isolation of emission source which keeps a selected hazard "physically" away from the worker and ventilation that strategically "adds" and "removes" air in the work environment. Ventilation can remove or dilute an air contaminant if designed properly. The design of a ventilation system must match the particular process and chemical or contaminant in use.

Employers may need to use multiple types of controls to prevent employee overexposure.

Individual protection measures, such as personal protective equipment











Eye and face protection

Safety glasses with side shields.

► Chemical goggles.

Contact lenses may pose a special hazard; soft contact lenses may absorb and concentrate irritants. A written policy document, describing the wearing of lenses or restrictions on use, should be created for each workplace or task. This should include a review of lens absorption and adsorption for the class of chemicals in use and an account of injury experience. Medical and first-aid personnel should be trained in their removal and suitable equipment should be readily available. In the event of chemical exposure, begin eye irrigation immediately and remove contact lens as soon as practicable.

Skin protection

See Hand protection below

- ► Wear chemical protective gloves, e.g. PVC.
- ▶ Wear safety footwear or safety gumboots, e.g. Rubber

The selection of suitable gloves does not only depend on the material, but also on further marks of quality which vary from manufacturer to manufacturer. Where the chemical is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

Hands/feet protection

The exact break through time for substances has to be obtained from the manufacturer of the protective gloves and has to be observed when making a final choice.

Personal hygiene is a key element of effective hand care. Gloves must only be worn on clean hands. After using gloves, hands should be washed and dried thoroughly. Application of a non-perfumed moisturiser is recommended.

Neoprene rubber gloves

· Nitrile rubber gloves (Note: Nitric acid penetrates nitrile gloves in a few minutes.)

Body protection

See Other protection below

Other protection

Overalls.

P.V.C apron.

Barrier cream.Skin cleansing cream.

► Eye wash unit.

Issue Date: 17/03/2023

OPAQUE PIGMENT GREY

Issue Date: 17/03/2023 Print Date: 08/06/2023

Respiratory protection

Type A-P Filter of sufficient capacity. (AS/NZS 1716 & 1715, EN 143:2000 & 149:2001, ANSI Z88 or national equivalent)

Where the concentration of gas/particulates in the breathing zone, approaches or exceeds the "Exposure Standard" (or ES), respiratory protection is required. Degree of protection varies with both face-piece and Class of filter; the nature of protection varies with Type of filter.

Required Minimum Protection Factor	Half-Face Respirator	Full-Face Respirator	Powered Air Respirator
up to 10 x ES	A-AUS P2	-	A-PAPR-AUS / Class 1 P2
up to 50 x ES	-	A-AUS / Class 1 P2	-
up to 100 x ES	-	A-2 P2	A-PAPR-2 P2 ^

^ - Full-face

 $A(A|I|Classes) = Organic \ vapours, \ B \ AUS \ or \ B1 = Acid \ gasses, \ B2 = Acid \ gas \ or \ hydrogen \ cyanide(HCN), \ B3 = Acid \ gas \ or \ hydrogen \ cyanide(HCN), \ E = Sulfur \ dioxide(SO2), \ G = Agricultural \ chemicals, \ K = Ammonia(NH3), \ Hg = Mercury, \ NO = Oxides \ of \ nitrogen, \ MB = Methyl \ bromide, \ AX = Low \ boiling \ point \ organic \ compounds(below \ 65 \ degC)$

- ▶ Cartridge respirators should never be used for emergency ingress or in areas of unknown vapour concentrations or oxygen content.
- The wearer must be warned to leave the contaminated area immediately on detecting any odours through the respirator. The odour may indicate that the mask is not functioning properly, that the vapour concentration is too high, or that the mask is not properly fitted. Because of these limitations, only restricted use of cartridge respirators is considered appropriate.
- Cartridge performance is affected by humidity. Cartridges should be changed after 2 hr of continuous use unless it is determined that the humidity is less than 75%, in which case, cartridges can be used for 4 hr. Used cartridges should be discarded daily, regardless of the length of time used

SECTION 9 Physical and chemical properties

Information on basic physical and chemical properties

Appearance	Gray liquid with slight odour; does not mix with water.		
Physical state	Liquid	Relative density (Water = 1)	1.79 @25C
Odour	Not Available	Partition coefficient n-octanol / water	Not Available
Odour threshold	Not Available	Auto-ignition temperature (°C)	Not Available
pH (as supplied)	Not Applicable	Decomposition temperature (°C)	Not Available
Melting point / freezing point (°C)	Not Available	Viscosity (cSt)	Not Available
Initial boiling point and boiling range (°C)	Not Available	Molecular weight (g/mol)	Not Applicable
Flash point (°C)	107.2	Taste	Not Available
Evaporation rate	Not Available	Explosive properties	Not Available
Flammability	Not Applicable	Oxidising properties	Not Available
Upper Explosive Limit (%)	Not Available	Surface Tension (dyn/cm or mN/m)	Not Available
Lower Explosive Limit (%)	Not Available	Volatile Component (%vol)	Negligible
Vapour pressure (kPa)	Not Available	Gas group	Not Available
Solubility in water	Immiscible	pH as a solution (1%)	Not Applicable
Vapour density (Air = 1)	Not Available	VOC g/L	Negligible

SECTION 10 Stability and reactivity

Reactivity	See section 7
Chemical stability	 Unstable in the presence of incompatible materials. Product is considered stable. Hazardous polymerisation will not occur.
Possibility of hazardous reactions	See section 7
Conditions to avoid	See section 7
Incompatible materials	See section 7
Hazardous decomposition products	See section 5

SECTION 11 Toxicological information

Information on toxicological effects

Inhaled	Inhalation hazard is increased at higher temperatures. Not normally a hazard due to non-volatile nature of product
Ingestion	Accidental ingestion of the material may be damaging to the health of the individual. Ingestion may result in nausea, abdominal irritation, pain and vomiting
Skin Contact	There is some evidence to suggest that the material may cause mild but significant inflammation of the skin either following direct contact or after a delay of some time. Repeated exposure can cause contact dermatitis which is characterised by redness, swelling and blistering. Open cuts, abraded or irritated skin should not be exposed to this material Entry into the blood-stream, through, for example, cuts, abrasions or lesions, may produce systemic injury with harmful effects. Examine the skin prior to the use of the material and ensure that any external damage is suitably protected.

Chemwatch: 9848799

Page 6 of 11 Issue Date: 17/03/2023 Version No: 10.1 Print Date: 08/06/2023 **OPAQUE PIGMENT GREY**

There is some evidence that material may produce eye irritation in some persons and produce eye damage 24 hours or more after instillation. Eve Moderate inflammation may be expected with redness; conjunctivitis may occur with prolonged exposure. The liquid may produce eye discomfort and is capable of causing temporary impairment of vision and/or transient eye inflammation, ulceration Chronic Substance accumulation, in the human body, may occur and may cause some concern following repeated or long-term occupational exposure. TOXICITY IRRITATION **OPAQUE PIGMENT GREY** Not Available Not Available TOXICITY IRRITATION dermal (hamster) LD50: >=10000 mg/kg[2] Eye: no adverse effect observed (not irritating)[1]titanium dioxide Inhalation(Rat) LC50: >2.28 mg/l4h^[1] Skin (human): 0.3 mg/3D (int)-mild 3 Skin: no adverse effect observed (not irritating)[1]Oral (Rat) LD50: >=2000 mg/kg[1] IRRITATION di-C9-11-alkyl phthalate, dermal (guinea pig) LD50: 10000 mg/kg^[2] Eye (rabbit): 500 mg/24h mild C10-rich Oral (Mouse) LD50; 1500 mg/kg^[2] Skin (rabbit): 500 mg/24h mild TOXICITY IRRITATION Dermal (rabbit) LD50: >2000 mg/kg^[1] Eye: no adverse effect observed (not irritating)[1] carbon black Oral (Rat) LD50: >2000 mg/kg[1] Skin: no adverse effect observed (not irritating)^[1] TOXICITY IRRITATION Inhalation(Rat) LC50: >2.3 mg/l4h[1] Eye: no adverse effect observed (not irritating)^[1] aluminium hydroxide Oral (Rat) LD50: >2000 mg/kg[1] Skin: no adverse effect observed (not irritating)[1] TOXICITY IRRITATION Eye (rabbit): non-irritating ** [Grace] dermal (rat) LD50: >2000 mg/kg^[1] Inhalation(Rat) LC50: >0.09<0.84 mg/l4h^[1] Eye: no adverse effect observed (not irritating) $^{[1]}$ silica amorphous Skin (rabbit): non-irritating * Oral (Rat) LD50: >1000 mg/kg^[1] Skin: no adverse effect observed (not irritating)[1] 1. Value obtained from Europe ECHA Registered Substances - Acute toxicity 2. Value obtained from manufacturer's SDS. Unless otherwise Legend: specified data extracted from RTECS - Register of Toxic Effect of chemical Substances * IUCLID Laboratory (in vitro) and animal studies show, exposure to the material may result in a possible risk of irreversible effects, with the possibility of producing mutation. Asthma-like symptoms may continue for months or even years after exposure to the material ends. This may be due to a non-allergic condition known as reactive airways dysfunction syndrome (RADS) which can occur after exposure to high levels of highly irritating compound. Main criteria for diagnosing RADS include the absence of previous airways disease in a non-atopic individual, with sudden onset of persistent asthma-like symptoms within minutes to hours of a documented exposure to the irritant. Other criteria for diagnosis of RADS include a reversible airflow pattern on lung function tests, moderate to severe bronchial hyperreactivity on methacholine challenge testing, and the lack of minimal lymphocytic inflammation, without eosinophilia. RADS (or asthma) following an irritating inhalation is an infrequent disorder with rates related to TITANIUM DIOXIDE the concentration of and duration of exposure to the irritating substance. On the other hand, industrial bronchitis is a disorder that occurs as a result of exposure due to high concentrations of irritating substance (often particles) and is completely reversible after exposure ceases. The disorder is characterized by difficulty breathing, cough and mucus production. Exposure to titanium dioxide is via inhalation, swallowing or skin contact. When inhaled, it may deposit in lung tissue and lymph nodes causing dysfunction of the lungs and immune system. Absorption by the stomach and intestines depends on the size of the particle. It penetrated only the outermost layer of the skin, suggesting that healthy skin may be an effective barrier. There is no substantive data on genetic damage, though cases have been reported in experimental animals. Studies have differing conclusions on its cancer-causing potential. The material may produce moderate eye irritation leading to inflammation. Repeated or prolonged exposure to irritants may produce conjunctivitis High Molecular Weight Phthalate Esters (HMWPEs) Category The HMWPE group includes chemically similar substances produced from alcohols. These substances have been demonstrated to have few biological effects. They demonstrate minimal acute toxicity, with effect on the liver and kidney at high doses. They also cause reproductive and developmental toxicity, also, liver cancer. They are readily metabolised and excreted primarily via the urine. Repeated doses may cause liver and DI-C9-11-ALKYL PHTHALATE, kidney damage, although the relevance to human health is questionable C10-RICH The material may produce peroxisome proliferation. Peroxisomes are single, membrane limited organelles in the cytoplasm that are found in the cells of animals, plants, fungi, and protozoa The material may be irritating to the eye, with prolonged contact causing inflammation. Repeated or prolonged exposure to irritants may produce conjunctivitis **CARBON BLACK** Inhalation (rat) TCLo: 50 mg/m3/6h/90D-I Nil reported Reports indicate high/prolonged exposures to amorphous silicas induced lung fibrosis in experimental animals; in some experiments these effects were reversible. [PATTYS] For silica amorphous: Derived No Adverse Effects Level (NOAEL) in the range of 1000 mg/kg/d. In humans, synthetic amorphous silica (SAS) is essentially non-toxic by mouth, skin or eyes, and by inhalation. Epidemiology studies show little SILICA AMORPHOUS evidence of adverse health effects due to SAS. Repeated exposure (without personal protection) may cause mechanical irritation of the eye and drying/cracking of the skin. When experimental animals inhale synthetic amorphous silica (SAS) dust, it dissolves in the lung fluid and is rapidly eliminated. If swallowed, the vast majority of SAS is excreted in the faeces and there is little accumulation in the body. Following absorption across the gut, SAS is eliminated via urine without modification in animals and humans. SAS is not expected to be broken down (metabolised) in mammals After ingestion, there is limited accumulation of SAS in body tissues and rapid elimination occurs. Intestinal absorption has not been calculated,

Chemwatch: 9848799 Version No: 10.1

OPAQUE PIGMENT GREY

Issue Date: 17/03/2023 Print Date: 08/06/2023

	but appears to be insignificant in animals and humans. The substance is classified by IARC as Group 3: NOT classifiable as to its carcinogenicity to humans. Evidence of carcinogenicity may be inadequate or limited in animal testing.				
TITANIUM DIOXIDE & CARBON BLACK & ALUMINIUM HYDROXIDE	No significant acute toxicological data identified in literature search.				
TITANIUM DIOXIDE & DI-C9-11-ALKYL PHTHALATE, C10-RICH	The material may cause skin irritation after prolonged or repeated exposure and may produce on contact skin redness, swelling, the production of vesicles, scaling and thickening of the skin.				
TITANIUM DIOXIDE & CARBON BLACK	WARNING: This substance has been classified by the IARC as Group 2B: Possibly Carcinogenic to Humans.				
Acute Toxicity	X Carcinogenicity	×			
Skin Irritation/Corrosion	X Reproductivity	×			
Serious Eye Damage/Irritation	✓ STOT - Single Exposure X				
Respiratory or Skin sensitisation	X STOT - Repeated Exposure	×			
Mutagenicity	X Aspiration Hazard	×			

Legend:

X − Data either not available or does not fill the criteria for classification
 ✓ − Data available to make classification

SECTION 12 Ecological information

Toxicity

	Endpoint	Test Duration (hr)		Species		Value	Source
OPAQUE PIGMENT GREY	Not Available	Not Available		Not Available		Not Available	Not Availabl
	Endpoint	Test Duration (hr)		Species		Value	Sourc
	BCF	1008h		Fish		<1.1-9.6	7
	LC50	96h	Fish			1.85-3.06mg/l	4
titanium dioxide	EC50	72h		Algae or other aquatic plants		3.75-7.58mg/l	4
	EC50	48h		Crustacea		1.9mg/l	2
	EC50	96h		Algae or other aquatic plants		179.05mg/l	2
	NOEC(ECx)	504h		Crustacea		0.02mg/l	4
	Endpoint	Test Duration (hr)		Species		Value	Source
	NOEC(ECx)	504h		Crustacea		>0.03mg/l	1
di-C9-11-alkyl phthalate, C10-rich	LC50	96h		Fish		>0.37mg/l	2
Cio-iicii	EC50	96h		Algae or other aquatic plants		>1.3mg/l	1
	EC50	48h		Crustacea		>0.18mg/l	1
	Endpoint	Test Duration (hr)	S	Species Value		ie	Source
	LC50	96h	F	Fish >100		0mg/l	2
carbon black	EC50	72h	А	Algae or other aquatic plants >0.2		?mg/l	2
	EC50	48h	Crustacea 33.0		76-41.968mg/l	4	
	NOEC(ECx)	24h	C	Crustacea 3200		0mg/l	1
	Endpoint	Test Duration (hr)		Species		Value	Source
	NOEC(ECx)	72h		Algae or other aquatic plants		>100mg/l	1
	EC50	72h		Algae or other aquatic plants		0.0169mg/l	2
aluminium hydroxide	EC50	96h		Algae or other aquatic plants		0.0054mg/l	2
	LC50	96h		Fish		0.57mg/l	2
	EC50	48h		Crustacea		>0.065mg/l	4
	Endpoint	Test Duration (hr)		Species		Value	Source
	EC0(ECx)	24h		Crustacea		>=10000mg/l	1
oilian amanuta.	EC50	96h		Algae or other aquatic plants		217.576mg/l	2
silica amorphous	EC50	72h		Algae or other aquatic plants		14.1mg/l	2
	LC50	96h		Fish		1033.016mg/l	2
	EC50	48h		Crustacea		>86mg/l	2
Legend:	Ecotox databas	I. IUCLID Toxicity Data 2. Europe ECH Se - Aquatic Toxicity Data 5. ECETOC A tion Data 8. Vendor Data					

 Chemwatch: 9848799
 Page 8 of 11
 Issue Date: 17/03/2023

 Version No: 10.1
 OPAQUE PIGMENT GREY
 Print Date: 08/06/2023

DO NOT discharge into sewer or waterways.

Persistence and degradability

Ingredient	Persistence: Water/Soil	Persistence: Air
titanium dioxide	HIGH	HIGH
silica amorphous	LOW	LOW

Bioaccumulative potential

Ingredient	Bioaccumulation
titanium dioxide	LOW (BCF = 10)
di-C9-11-alkyl phthalate, C10-rich	HIGH (BCF = 3500)
silica amorphous	LOW (LogKOW = 0.5294)

Mobility in soil

Ingredient	Mobility	
titanium dioxide	LOW (KOC = 23.74)	
silica amorphous	LOW (KOC = 23.74)	

SECTION 13 Disposal considerations

Waste treatment methods

Product / Packaging disposal

- ▶ DO NOT allow wash water from cleaning or process equipment to enter drains
- ▶ It may be necessary to collect all wash water for treatment before disposal.
- ▶ In all cases disposal to sewer may be subject to local laws and regulations and these should be considered first.
- Where in doubt contact the responsible authority.
- ▶ Recycle wherever possible or consult manufacturer for recycling options.
- ▶ Consult State Land Waste Authority for disposal.
- ▶ Bury or incinerate residue at an approved site.
- · Recycle containers if possible, or dispose of in an authorised landfill.

Ensure that the hazardous substance is disposed in accordance with the Hazardous Substances (Disposal) Notice 2017

Disposal Requirements

Packages that have been in direct contact with the hazardous substance must be only disposed if the hazardous substance was appropriately removed and cleaned out from the package. The package must be disposed according to the manufacturer's directions taking into account the material it is made of. Packages which hazardous content have been appropriately treated and removed may be recycled.

The hazardous substance must only be disposed if it has been treated by a method that changed the characteristics or composition of the substance and it is no longer hazardous. Only dispose to the environment if a tolerable exposure limit has been set for the substance.

Only deposit the hazardous substance into or onto a landfill or sewage facility or incinerator, where the hazardous substance can be handled and treated appropriately.

SECTION 14 Transport information

Labels Required

Marine Pollutant	NO
HAZCHEM	Not Applicable

Land transport (UN): NOT REGULATED FOR TRANSPORT OF DANGEROUS GOODS

Air transport (ICAO-IATA / DGR): NOT REGULATED FOR TRANSPORT OF DANGEROUS GOODS

Sea transport (IMDG-Code / GGVSee): NOT REGULATED FOR TRANSPORT OF DANGEROUS GOODS

Transport in bulk according to Annex II of MARPOL and the IBC code

Not Applicable

Transport in bulk in accordance with MARPOL Annex V and the IMSBC Code

Product name	Group	
titanium dioxide	Not Available	
di-C9-11-alkyl phthalate, C10-rich	Not Available	
carbon black	Not Available	
aluminium hydroxide	Not Available	
silica amorphous	Not Available	

Transport in bulk in accordance with the IGC Code

Product name	Ship Type
titanium dioxide	Not Available

Chemwatch: 9848799 Version No: 10.1

OPAQUE PIGMENT GREY

Issue Date: 17/03/2023 Print Date: 08/06/2023

Product name	Ship Type
di-C9-11-alkyl phthalate, C10-rich	Not Available
carbon black	Not Available
aluminium hydroxide	Not Available
silica amorphous	Not Available

SECTION 15 Regulatory information

Safety, health and environmental regulations / legislation specific for the substance or mixture

This substance is to be managed using the conditions specified in an applicable Group Standard

HSR Number	Group Standard
HSR002521	Animal Nutritional and Animal Care Products Group Standard 2020
HSR002503	Additives Process Chemicals and Raw Materials Subsidiary Hazard Group Standard 2020
HSR002571	Fertilisers Subsidiary Hazard Group Standard 2020
HSR100757	Veterinary Medicines Limited Pack Size Finished Dose Group Standard 2020
HSR100758	Veterinary Medicines Non dispersive Closed System Application Group Standard 2020
HSR100759	Veterinary Medicines Non dispersive Open System Application Group Standard 2020
HSR100592	Agricultural Compounds Special Circumstances Group Standard 2020
HSR100756	Active Ingredients for Use in the Manufacture of Agricultural Compounds Group Standard 2020

Please refer to Section 8 of the SDS for any applicable tolerable exposure limit or Section 12 for environmental exposure limit.

titanium dioxide is found on the following regulatory lists

Chemical Footprint Project - Chemicals of High Concern List

International Agency for Research on Cancer (IARC) - Agents Classified by the IARC Monographs

International Agency for Research on Cancer (IARC) - Agents Classified by the IARC Monographs - Group 2B: Possibly carcinogenic to humans

di-C9-11-alkyl phthalate, C10-rich is found on the following regulatory lists

Chemical Footprint Project - Chemicals of High Concern List

carbon black is found on the following regulatory lists

Chemical Footprint Project - Chemicals of High Concern List

International Agency for Research on Cancer (IARC) - Agents Classified by the IARC Monographs

International Agency for Research on Cancer (IARC) - Agents Classified by the IARC Monographs - Group 2B: Possibly carcinogenic to humans International WHO List of Proposed Occupational Exposure Limit (OEL) Values for

Manufactured Nanomaterials (MNMS) New Zealand Approved Hazardous Substances with controls

aluminium hydroxide is found on the following regulatory lists

International WHO List of Proposed Occupational Exposure Limit (OEL) Values for Manufactured Nanomaterials (MNMS)

New Zealand Inventory of Chemicals (NZIoC)

silica amorphous is found on the following regulatory lists

Chemical Footprint Project - Chemicals of High Concern List

International WHO List of Proposed Occupational Exposure Limit (OEL) Values for Manufactured Nanomaterials (MNMS)

New Zealand Approved Hazardous Substances with controls

International WHO List of Proposed Occupational Exposure Limit (OEL) Values for Manufactured Nanomaterials (MNMS)

New Zealand Inventory of Chemicals (NZIoC)

New Zealand Workplace Exposure Standards (WES)

New Zealand Inventory of Chemicals (NZIoC)

New Zealand Hazardous Substances and New Organisms (HSNO) Act - Classification of Chemicals

New Zealand Hazardous Substances and New Organisms (HSNO) Act - Classification of Chemicals - Classification Data

New Zealand Inventory of Chemicals (NZIoC)

New Zealand Workplace Exposure Standards (WES)

New Zealand Workplace Exposure Standards (WES)

International Agency for Research on Cancer (IARC) - Agents Classified by the IARC Monographs - Not Classified as Carcinogenic

New Zealand Hazardous Substances and New Organisms (HSNO) Act - Classification of Chemicals

New Zealand Hazardous Substances and New Organisms (HSNO) Act - Classification of Chemicals - Classification Data

New Zealand Inventory of Chemicals (NZIoC)

New Zealand Workplace Exposure Standards (WES)

Hazardous Substance Location

Subject to the Health and Safety at Work (Hazardous Substances) Regulations 2017.

Hazard Class	Quantities
Not Applicable	Not Applicable

Certified Handler

Subject to Part 4 of the Health and Safety at Work (Hazardous Substances) Regulations 2017.

Class of substance	Quantities
Not Applicable	Not Applicable

Refer Group Standards for further information

Maximum quantities of certain hazardous substances permitted on passenger service vehicles

Subject to Regulation 13.14 of the Health and Safety at Work (Hazardous Substances) Regulations 2017.

Hazard Class	Gas (aggregate water capacity in mL)	Liquid (L)	Solid (kg)	Maximum quantity per package for each classification
--------------	--------------------------------------	------------	------------	--

OPAQUE PIGMENT GREY

Hazard Class
Gas (aggregate water capacity in mL)

Not Applicable

Tracking Requirements

Not Applicable

Chemwatch: 9848799

Version No: 10.1

National Inventory Status

National Inventory	Status	
Australia - AIIC / Australia Non-Industrial Use	Yes	
Canada - DSL	Yes	
Canada - NDSL	No (di-C9-11-alkyl phthalate, C10-rich; carbon black; aluminium hydroxide)	
China - IECSC	Yes	
Europe - EINEC / ELINCS / NLP	Yes	
Japan - ENCS	Yes	
Korea - KECI	Yes	
New Zealand - NZIoC	Yes	
Philippines - PICCS	Yes	
USA - TSCA	Yes	
Taiwan - TCSI	Yes	
Mexico - INSQ	Yes	
Vietnam - NCI	Yes	
Russia - FBEPH	No (di-C9-11-alkyl phthalate, C10-rich)	
Legend:	Yes = All CAS declared ingredients are on the inventory No = One or more of the CAS listed ingredients are not on the inventory. These ingredients may be exempt or will require registration.	

SECTION 16 Other information

Revision Date	17/03/2023
Initial Date	29/11/2013

SDS Version Summary

Version	Date of Update	Sections Updated
8.1	23/12/2022	Classification review due to GHS Revision change.
10.1	17/03/2023	Hazards identification - Classification, Identification of the substance / mixture and of the company / undertaking - Supplier Information, Identification of the substance / mixture and of the company / undertaking - Synonyms, Name

Other information

Classification of the preparation and its individual components has drawn on official and authoritative sources as well as independent review by the Chemwatch Classification committee using available literature references.

The SDS is a Hazard Communication tool and should be used to assist in the Risk Assessment. Many factors determine whether the reported Hazards are Risks in the workplace or other settings. Risks may be determined by reference to Exposures Scenarios. Scale of use, frequency of use and current or available engineering controls must be considered.

Definitions and abbreviations

PC - TWA: Permissible Concentration-Time Weighted Average

PC - STEL: Permissible Concentration-Short Term Exposure Limit

IARC: International Agency for Research on Cancer

ACGIH: American Conference of Governmental Industrial Hygienists

STEL: Short Term Exposure Limit

TEEL: Temporary Emergency Exposure Limit₀

IDLH: Immediately Dangerous to Life or Health Concentrations

ES: Exposure Standard

OSF: Odour Safety Factor

NOAEL :No Observed Adverse Effect Level

LOAEL: Lowest Observed Adverse Effect Level

TLV: Threshold Limit Value LOD: Limit Of Detection

OTV: Odour Threshold Value

BCF: BioConcentration Factors

BEI: Biological Exposure Index

AIIC: Australian Inventory of Industrial Chemicals

DSL: Domestic Substances List

NDSL: Non-Domestic Substances List

IECSC: Inventory of Existing Chemical Substance in China

EINECS: European INventory of Existing Commercial chemical Substances

ELINCS: European List of Notified Chemical Substances

NLP: No-Longer Polymers

ENCS: Existing and New Chemical Substances Inventory

KECI: Korea Existing Chemicals Inventory NZIoC: New Zealand Inventory of Chemicals

PICCS: Philippine Inventory of Chemicals and Chemical Substances

TSCA: Toxic Substances Control Act

Issue Date: 17/03/2023

Print Date: 08/06/2023

Chemwatch: 9848799 Page 11 of 11 Issue Date: 17/03/2023 Version No: 10.1 Print Date: 08/06/2023 **OPAQUE PIGMENT GREY**

TCSI: Taiwan Chemical Substance Inventory INSQ: Inventario Nacional de Sustancias Químicas

NCI: National Chemical Inventory FBEPH: Russian Register of Potentially Hazardous Chemical and Biological Substances

This document is copyright.

Apart from any fair dealing for the purposes of private study, research, review or criticism, as permitted under the Copyright Act, no part may be reproduced by any process without written permission from CHEMWATCH.

TEL (+61 3) 9572 4700.