

# STONE COAT COUNTERTOPS

**SUBJECT: USDA ACCEPTABLE EPOXY**

To Whom It May Concern,

The following products meet the performance requirements of the U.S.D.A. as a topcoat for countertops and concrete sealer:

Epoxies: Stone Coat Countertops Epoxy Resin & Epoxy Hardener  
and Art Coat Resin & Hardener

These products are manufactured and supplied by:

Stone Coat Countertops, Inc.  
413 Union Ave  
Grants Pass, OR 97527

These products are suitable and appropriate as topcoat for countertops and concrete coatings when used according to our label instructions and in accordance with the specifications to be offered in this letter. Their use will not result in the adulterations of any food products via incidental contact when used and applied as we, the manufacturer, stipulate.

Once cured, these products will stand up to rigorous cleaning and dampness and are grease and acid resistant. They are impervious to moisture and contain no known carcinogens, mutagens or tetragens classified as hazardous substances. They are not pesticides nor do they have any known pesticide characteristics. If necessary, we are prepared to supply the federal safety and inspector service with a complete chemical list of the materials used to manufacture these products.

These products should be applied when the temperature of ambient and surface to be coated is 65°F or above. For U.S.D.A. performance, all coats of these products should be allowed to cure at temperatures of 65°F or above.

Apply epoxies at the rate of 30-300 square feet per gallon depending on substrate or between 4.5-50 mils wet film thickness.

A copy of this letter should be tendered to the applicator and also for your files.

If you have any questions, please call: (541) 450-1976

Sincerely,  
Stone Coat Countertops Inc.