

# **F-125 PART B BARNES PRODUCTS PTY LTD**

Chemwatch: 5246-49

Safety Data Sheet according to the Health and Safety at Work (Hazardous Substances) Regulations 2017

Issue Date: 20/03/2023 Print Date: 15/06/2023 S.GHS.NZL.EN.E

# SECTION 1 Identification of the substance / mixture and of the company / undertaking

#### **Product Identifier**

Version No: 8.1

Product name	F-125 PART B	
Chemical Name	Chemical Name Not Applicable	
Synonyms	-125 REV 1 PART B	
Proper shipping name	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (contains diethyltoluenediamine)	
Chemical formula	Not Applicable	
Other means of identification Not Available		

#### Relevant identified uses of the substance or mixture and uses advised against

Relevant identified uses Polyurethane curative.

#### Details of the manufacturer or supplier of the safety data sheet

Registered company name	BARNES PRODUCTS PTY LTD	
Address	5 GREENHILLS AVE MOOREBANK NSW 2170 Australia	
Telephone	arnes Australia +612 9793 7555 Mon-Fri 8am-4:30pm	
Fax	Barnes Australia +612 9793 7091	
Website	www.barnesnz.co.nz	
Email	sales@barnes.com.au	

#### **Emergency telephone number**

Association / Organisation	New Zealand Poisons Information Centre	
Emergency telephone numbers	Barnes NZ +649 9731 816 - Monday-Thursday 9am-5pm Friday 9am-4.30pm	
Other emergency telephone numbers	New Zealand Poisons Information Centre 0800 764 766 After Hours	

# **SECTION 2 Hazards identification**

## Classification of the substance or mixture

Classification [1] Specific Target Organ Toxicity - Repeated Exposure Category 2, Hazardous to the Aquatic Environment Long-Term Hazard Category 2		
Legend:	Legend: 1. Classified by Chemwatch; 2. Classification drawn from CCID EPA NZ; 3. Classification drawn from Regulation (EU) No 1272/2008 - Annex	
Determined by Chemwatch using GHS/HSNO criteria	6.9B, 9.1B	

# Label elements

Hazard pictogram(s)





Signal word Warning

nazaru statement(s)	
H373 May cause damage to organs through prolonged or repeated exposure.	
H411	Toxic to aquatic life with long lasting effects.

#### Precautionary statement(s) Prevention

P260	Do not breathe mist/vapours/spray.
P273	Avoid release to the environment.

Version No: 8.1 F-125 PART B

Issue Date: 20/03/2023 Print Date: 15/06/2023

#### Precautionary statement(s) Response

• • • • • • • • • • • • • • • • • • • •	•
P314	Get medical advice/attention if you feel unwell.
P391	Collect spillage.

#### Precautionary statement(s) Storage

Not Applicable

#### Precautionary statement(s) Disposal

P501 Dispose of contents/container to authorised hazardous or special waste collection point in accordance with any local regulation.

#### **SECTION 3 Composition / information on ingredients**

#### Substances

See section below for composition of Mixtures

#### **Mixtures**

CAS No	%[weight]	Name
Not Available	>60	polyether polyol mixture
68479-98-1	<5	<u>diethyltoluenediamine</u>
Legend:	Classified by Chemwatch; 2. Classification drawn from CCID EPA NZ; 3. Classification drawn from Regulation (EU) No 1272/2008 - Annex VI;     Classification drawn from C&L * EU IOELVs available	

#### **SECTION 4 First aid measures**

#### Description of first aid measures

Eye Contact	If this product comes in contact with the eyes:  Immediately hold eyelids apart and flush the eye continuously with running water.  Ensure complete irrigation of the eye by keeping eyelids apart and away from eye and moving the eyelids by occasionally lifting the upper and lower lids.  Continue flushing until advised to stop by the Poisons Information Centre or a doctor, or for at least 15 minutes.  Transport to hospital or doctor without delay.  Removal of contact lenses after an eye injury should only be undertaken by skilled personnel.
If skin contact occurs:  If skin contact  If skin contact occurs:  If s	
Inhalation Remove patient to fresh air and seek medical attention.	
Ingestion	<ul> <li>If swallowed do NOT induce vomiting.</li> <li>If vomiting occurs, lean patient forward or place on left side (head-down position, if possible) to maintain open airway and prevent aspiration.</li> <li>Observe the patient carefully.</li> <li>Never give liquid to a person showing signs of being sleepy or with reduced awareness; i.e. becoming unconscious.</li> <li>Give water to rinse out mouth, then provide liquid slowly and as much as casualty can comfortably drink.</li> <li>Seek medical advice.</li> <li>If patient is unconscious, DO NOT attempt to give fluids by mouth.</li> </ul>

#### Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

#### **SECTION 5 Firefighting measures**

# Extinguishing media

- ▶ Foam
- Dry chemical powder.
- ► BCF (where regulations permit).
- Carbon dioxide.
- Water spray or fog Large fires only.

#### Special hazards arising from the substrate or mixture

Fire Incompatibility Avoid contamination with oxidising agents i.e. nitrates, oxidising acids, chlorine bleaches, pool chlorine etc. as ignition may result

## Advice for firefighters

- Alert Fire Brigade and tell them location and nature of hazard.
- Wear breathing apparatus plus protective gloves.
- Prevent, by any means available, spillage from entering drains or water courses.
- Use water delivered as a fine spray to control fire and cool adjacent area.
- ▶ DO NOT approach containers suspected to be hot.
- Cool fire exposed containers with water spray from a protected location.
- If safe to do so, remove containers from path of fire.

#### Combustible.

Fire Fighting

Fire/Explosion Hazard

- Slight fire hazard when exposed to heat or flame.
- Heating may cause expansion or decomposition leading to violent rupture of containers.
- On combustion, may emit toxic fumes of carbon monoxide (CO).
- May emit acrid smoke.
- Mists containing combustible materials may be explosive.

Chemwatch: 5246-49 Page 3 of 10 Issue Date: 20/03/2023 Version No: 8.1 Print Date: 15/06/2023 F-125 PART B

> Combustion products include: carbon dioxide (CO2) nitrogen oxides (NOx) other pyrolysis products typical of burning organic material. May emit poisonous fumes. May emit corrosive fumes.

#### **SECTION 6 Accidental release measures**

#### Personal precautions, protective equipment and emergency procedures

See section 8

#### **Environmental precautions**

See section 12

# Methods and material for containment and cleaning up

Minor Spills	<ul> <li>Remove all ignition sources.</li> <li>Clean up all spills immediately.</li> <li>Avoid breathing vapours and contact with skin and eyes.</li> <li>Control personal contact with the substance, by using protective equipment.</li> <li>Contain and absorb spill with sand, earth, inert material or vermiculite.</li> <li>Wipe up.</li> <li>Place in a suitable, labelled container for waste disposal.</li> </ul>
Major Spills	Moderate hazard.  Clear area of personnel and move upwind.  Alert Fire Brigade and tell them location and nature of hazard.  Wear breathing apparatus plus protective gloves.  Prevent, by any means available, spillage from entering drains or water course.  No smoking, naked lights or ignition sources.  Increase ventilation.

Personal Protective Equipment advice is contained in Section 8 of the SDS.

# **SECTION 7 Handling and storage**

Precautions for safe handling		
Safe handling	<ul> <li>Avoid all personal contact, including inhalation.</li> <li>Wear protective clothing when risk of exposure occurs.</li> <li>Use in a well-ventilated area.</li> <li>Prevent concentration in hollows and sumps.</li> <li>DO NOT enter confined spaces until atmosphere has been checked.</li> <li>Avoid smoking, naked lights or ignition sources.</li> <li>Avoid contact with incompatible materials.</li> <li>DO NOT allow clothing wet with material to stay in contact with skin</li> </ul>	
Other information	<ul> <li>Store in original containers.</li> <li>Keep containers securely sealed.</li> <li>No smoking, naked lights or ignition sources.</li> <li>Store in a cool, dry, well-ventilated area.</li> <li>Store away from incompatible materials and foodstuff containers.</li> <li>Protect containers against physical damage and check regularly for leaks.</li> <li>Observe manufacturer's storage and handling recommendations contained within this SDS.</li> </ul>	

#### Conditions for safe storage, including any incompatibilities

Suitable container  • Metal can or drum • Packaging as recommended by manufacturer. • Check all containers are clearly labelled and free from leaks.	
Storage incompatibility	Avoid reaction with oxidising agents isocyanates

# **SECTION 8 Exposure controls / personal protection**

## **Control parameters**

Occupational Exposure Limits (OEL)

INGREDIENT DATA

Not Available

**Emergency Limits** 

Ingredient	TEEL-1	TEEL-2		TEEL-3
F-125 PART B	Not Available	Not Available		Not Available
Ingredient	Original IDLH		Revised IDLH	
Ingredient diethyltoluenediamine	Original IDLH  Not Available		Revised IDLH  Not Available	

Ħ				
	Occu	national	Exposure	Randing
	Occu	pational	Lyboanie	Danuing

Ingredient	Occupational Exposure Band Rating	Occupational Exposure Band Limit
diethyltoluenediamine	E	≤ 0.1 ppm

F-125 PART B

Issue Date: **20/03/2023**Print Date: **15/06/2023** 

Ingredient	Occupational Exposure Band Rating	Occupational Exposure Band Limit
Notes:	Occupational exposure banding is a process of assigning chemicals into s adverse health outcomes associated with exposure. The output of this pro range of exposure concentrations that are expected to protect worker hea	ocess is an occupational exposure band (OEB), which corresponds to a

#### **Exposure controls**

# Appropriate engineering controls

Engineering controls are used to remove a hazard or place a barrier between the worker and the hazard. Well-designed engineering controls can be highly effective in protecting workers and will typically be independent of worker interactions to provide this high level of protection. The basic types of engineering controls are:

Process controls which involve changing the way a job activity or process is done to reduce the risk.

Enclosure and/or isolation of emission source which keeps a selected hazard "physically" away from the worker and ventilation that strategically "adds" and "removes" air in the work environment. Ventilation can remove or dilute an air contaminant if designed properly. The design of a ventilation system must match the particular process and chemical or contaminant in use.

Employers may need to use multiple types of controls to prevent employee overexposure.

# Individual protection measures, such as personal protective equipment











# Eye and face protection

- Safety glasses with side shields.
- ► Chemical goggles. [AS/NZS 1337.1, EN166 or national equivalent]
- Contact lenses may pose a special hazard; soft contact lenses may absorb and concentrate irritants. A written policy document, describing the wearing of lenses or restrictions on use, should be created for each workplace or task. This should include a review of lens absorption and adsorption for the class of chemicals in use and an account of injury experience. Medical and first-aid personnel should be trained in their removal and suitable equipment should be readily available. In the event of chemical exposure, begin eye irrigation immediately and remove contact lens as soon as practicable.

#### Skin protection

#### See Hand protection below

- Wear chemical protective gloves, e.g. PVC.
- ► Wear safety footwear or safety gumboots, e.g. Rubber

#### NOTE:

- The material may produce skin sensitisation in predisposed individuals. Care must be taken, when removing gloves and other protective equipment, to avoid all possible skin contact.
- Contaminated leather items, such as shoes, belts and watch-bands should be removed and destroyed.

#### Hands/feet protection

The selection of suitable gloves does not only depend on the material, but also on further marks of quality which vary from manufacturer to manufacturer. Where the chemical is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

The exact break through time for substances has to be obtained from the manufacturer of the protective gloves and has to be observed when making a final choice.

Personal hygiene is a key element of effective hand care. Gloves must only be worn on clean hands. After using gloves, hands should be washed and dried thoroughly. Application of a non-perfumed moisturiser is recommended.

#### **Body protection**

#### See Other protection below

# Other protection

- Overalls.P.V.C apron.
- Barrier cream.
- Barrier cream.Skin cleansing cream.
- Eye wash unit.

# Respiratory protection

Type AK-P Filter of sufficient capacity. (AS/NZS 1716 & 1715, EN 143:2000 & 149:2001, ANSI Z88 or national equivalent)

Selection of the Class and Type of respirator will depend upon the level of breathing zone contaminant and the chemical nature of the contaminant. Protection Factors (defined as the ratio of contaminant outside and inside the mask) may also be important.

Required minimum protection factor	Maximum gas/vapour concentration present in air p.p.m. (by volume)	Half-face Respirator	Full-Face Respirator
up to 10	1000	AK-AUS / Class1 P2	-
up to 50	1000	-	AK-AUS / Class 1 P2
up to 50	5000	Airline *	-
up to 100	5000	-	AK-2 P2
up to 100	10000	-	AK-3 P2
100+			Airline**

\* - Continuous Flow \*\* - Continuous-flow or positive pressure demand

A(All classes) = Organic vapours, B AUS or B1 = Acid gasses, B2 = Acid gas or hydrogen cyanide(HCN), B3 = Acid gas or hydrogen cyanide(HCN), E = Sulfur dioxide(SO2), G = Agricultural chemicals, K = Ammonia(NH3), Hg = Mercury, NO = Oxides of nitrogen, MB = Methyl bromide, AX = Low boiling point organic compounds(below 65 degC)

- Cartridge respirators should never be used for emergency ingress or in areas of unknown vapour concentrations or oxygen content.
- The wearer must be warned to leave the contaminated area immediately on detecting any odours through the respirator. The odour may indicate that the mask is not functioning properly, that the vapour concentration is too high, or that the mask is not properly fitted. Because of these limitations, only restricted use of cartridge respirators is considered appropriate.
- Cartridge performance is affected by humidity. Cartridges should be changed after 2 hr of continuous use unless it is determined that the humidity is less than 75%, in which case, cartridges can be used for 4 hr. Used cartridges should be discarded daily, regardless of the length of time used

#### **SECTION 9 Physical and chemical properties**

#### Information on basic physical and chemical properties

Appearance

Pale amber liquid with slight amine odour; slightly mixes with water.

Chemwatch: **5246-49**Version No: **8.1** 

F-125 PART B

Issue Date: 20/03/2023 Print Date: 15/06/2023

Physical state	Liquid	Relative density (Water = 1)	1.014 @25C
Odour	Not Available	Partition coefficient n-octanol / water	Not Available
Odour threshold	Not Available	Auto-ignition temperature (°C)	Not Available
pH (as supplied)	Not Available	Decomposition temperature (°C)	Not Available
Melting point / freezing point (°C)	Not Available	Viscosity (cSt)	998.790 @25C
Initial boiling point and boiling range (°C)	Not Available	Molecular weight (g/mol)	Not Applicable
Flash point (°C)	>182.2 (PMCC)	Taste	Not Available
Evaporation rate	Not Available	Explosive properties	Not Available
Flammability	Not Applicable	Oxidising properties	Not Available
Upper Explosive Limit (%)	Not Available	Surface Tension (dyn/cm or mN/m)	Not Available
Lower Explosive Limit (%)	Not Available	Volatile Component (%vol)	0.16
Vapour pressure (kPa)	Not Available	Gas group	Not Available
Solubility in water	Partly miscible	pH as a solution (1%)	Not Available
Vapour density (Air = 1)	Not Available	VOC g/L	<1.630

# **SECTION 10 Stability and reactivity**

Reactivity	See section 7
Chemical stability	<ul> <li>Unstable in the presence of incompatible materials.</li> <li>Product is considered stable.</li> <li>Hazardous polymerisation will not occur.</li> </ul>
Possibility of hazardous reactions	See section 7
Conditions to avoid	See section 7
Incompatible materials	See section 7
Hazardous decomposition products	See section 5

# **SECTION 11 Toxicological information**

Information	on	toxicological	effects

Inhaled	The material is not thought to produce adverse health effects or irritation of the respiratory tract (as classified by EC Directives using animal models). Nevertheless, good hygiene practice requires that exposure be kept to a minimum and that suitable control measures be used in an occupational setting.
Ingestion	The material has <b>NOT</b> been classified by EC Directives or other classification systems as "harmful by ingestion". This is because of the lack of corroborating animal or human evidence.
Skin Contact	The material may cause skin irritation after prolonged or repeated exposure and may produce on contact skin redness, swelling, the production of vesicles, scaling and thickening of the skin.  Open cuts, abraded or irritated skin should not be exposed to this material  Entry into the blood-stream, through, for example, cuts, abrasions or lesions, may produce systemic injury with harmful effects. Examine the skin prior to the use of the material and ensure that any external damage is suitably protected.
Еуе	The material may be irritating to the eye, with prolonged contact causing inflammation. Repeated or prolonged exposure to irritants may produce conjunctivitis.
Chronic	Substance accumulation, in the human body, may occur and may cause some concern following repeated or long-term occupational exposure. There is some evidence that inhaling this product is more likely to cause a sensitisation reaction in some persons compared to the general population.  There is limited evidence that, skin contact with this product is more likely to cause a sensitisation reaction in some persons compared to the general population.  Inhalation of epoxy resin amine hardeners (including polyamines and amine adducts) may produce bronchospasm and coughing episodes lasting several days after cessation of the exposure. Even faint traces of these vapours may trigger an intense reaction in individuals showing "amine asthma".  Amine epoxy-curing agents (hardeners) may produce primary skin irritation and sensitisation dermatitis in predisposed individuals. Cutaneous reactions include erythema, intolerable itching and severe facial swelling.

F-125 PART B	TOXICITY	IRRITATION
	Not Available	Not Available
	TOXICITY	IRRITATION
	Dermal (rabbit) LD50: >700 mg/kg <sup>[2]</sup>	Eye (rabbit): moderate-SEVERE [Manufacturer]
diethyltoluenediamine	Inhalation(Rat) LC50: >0.307 mg/L4h <sup>[1]</sup>	
	Oral (Rat) LD50: ~723 mg/kg <sup>[1]</sup>	
Legend:	Nalue obtained from Europe ECHA Registered Substant     specified data extracted from RTECS - Register of Toxic E	nces - Acute toxicity 2. Value obtained from manufacturer's SDS. Unless otherwise

Page 6 of 10 F-125 PART B Issue Date: **20/03/2023**Print Date: **15/06/2023** 

Oral (rat) LD50: 470-540 mg/kg Skin (rabbit): slight
The material may produce severe irritation to the eye causing pronounced inflammation. Repeated or prolonged exposure to irritants may produce conjunctivitis.

p-Phenylenediamine is oxidised by the liver microsomal enzymes (S9). Pure p-phenylenediamine does not cause mutations, but after it is oxidized, it does.

Acute Toxicity	×	Carcinogenicity	×
Skin Irritation/Corrosion	×	Reproductivity	×
Serious Eye Damage/Irritation	×	STOT - Single Exposure	×
Respiratory or Skin sensitisation	×	STOT - Repeated Exposure	<b>✓</b>
Mutagenicity	×	Aspiration Hazard	×

Legend:

💢 – Data either not available or does not fill the criteria for classification

Data available to make classification

#### **SECTION 12 Ecological information**

DIETHYLTOLUENEDIAMINE

#### **Toxicity**

F-125 PART B	Endpoint	Test Duration (hr)	Species	Value	Source
	Not Available	Not Available	Not Available	Not Available	Not Available
	Endpoint	Test Duration (hr)	Species	Value	Source
	EC0(ECx)	48h	Crustacea	0.3mg/l	2
diethyltoluenediamine	LC50	96h	Fish	~183mg/l	2
	EC50	96h	Algae or other aquatic plants	~1.157mg/l	2
	EC50	48h	Crustacea	0.5mg/l	2
Legend:	Ecotox databa	n 1. IUCLID Toxicity Data 2. Europe ECHA Register nse - Aquatic Toxicity Data 5. ECETOC Aquatic Haz ntion Data 8. Vendor Data	•		

Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

DO NOT discharge into sewer or waterways

#### Persistence and degradability

Ingredient	Persistence: Water/Soil	Persistence: Air	
	No Data available for all ingredients	No Data available for all ingredients	

#### Bioaccumulative potential

Ingredient	Bioaccumulation
	No Data available for all ingredients

# Mobility in soil

Ingredient	Mobility
	No Data available for all ingredients

#### **SECTION 13 Disposal considerations**

#### Waste treatment methods

Product / Packaging disposal

- ▶ DO NOT allow wash water from cleaning or process equipment to enter drains.
- It may be necessary to collect all wash water for treatment before disposal.
- In all cases disposal to sewer may be subject to local laws and regulations and these should be considered first.
- Where in doubt contact the responsible authority.
  - ▶ Recycle wherever possible or consult manufacturer for recycling options.
  - Consult State Land Waste Authority for disposal
     Bury or incinerate residue at an approved site.
  - Recycle containers if possible, or dispose of in an authorised landfill.

Ensure that the hazardous substance is disposed in accordance with the Hazardous Substances (Disposal) Notice 2017

#### **Disposal Requirements**

Packages that have been in direct contact with the hazardous substance must be only disposed if the hazardous substance was appropriately removed and cleaned out from the package. The package must be disposed according to the manufacturer's directions taking into account the material it is made of. Packages which hazardous content have been appropriately treated and removed may be recycled.

The hazardous substance must only be disposed if it has been treated by a method that changed the characteristics or composition of the substance and it is no longer hazardous. Only dispose to the environment if a tolerable exposure limit has been set for the substance.

Only deposit the hazardous substance into or onto a landfill or sewage facility or incinerator, where the hazardous substance can be handled and treated appropriately.

F-125 PART B

Issue Date: **20/03/2023**Print Date: **15/06/2023** 

# **SECTION 14 Transport information**

#### **Labels Required**



#### Marine Pollutant



•3Z

HAZCHEM

# Land transport (UN)

UN number or ID number	3082			
UN proper shipping name	ENVIRONMENTALLY	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (contains diethyltoluenediamine)		
Transport hazard class(es)	Class 9 Subsidiary risk N	lot Applicable		
Packing group	III			
Environmental hazard	Environmentally hazar	dous		
Special precautions for user	Special provisions Limited quantity	274; 331; 335; 375 5 L		

# Air transport (ICAO-IATA / DGR)

UN number	3082			
UN proper shipping name	Environmentally hazardous substance, liquid, n.o.s. (contains diethyltoluenediamine)			
Transport hazard class(es)	ICAO/IATA Class ICAO / IATA Subrisk ERG Code	9 sk Not Applicable 9L		
Packing group	III			
Environmental hazard	Environmentally hazardous			
Special precautions for user	Special provisions  Cargo Only Packing Instructions  Cargo Only Maximum Qty / Pack  Passenger and Cargo Packing Instructions  Passenger and Cargo Maximum Qty / Pack  Passenger and Cargo Limited Quantity Packing Instructions  Passenger and Cargo Limited Maximum Qty / Pack		A97 A158 A197 A215 964 450 L 964 450 L Y964 30 kg G	

# Sea transport (IMDG-Code / GGVSee)

UN number	3082		
UN proper shipping name	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (contains diethyltoluenediamine)		
Transport hazard class(es)	IMDG Class 9 IMDG Subrisk No	ot Applicable	
Packing group	III		
Environmental hazard	Marine Pollutant		
Special precautions for user	EMS Number Special provisions Limited Quantities	F-A, S-F 274 335 969 5 L	

# Transport in bulk according to Annex II of MARPOL and the IBC code

Not Applicable

# Transport in bulk in accordance with MARPOL Annex V and the IMSBC Code

Product name	Group
diethyltoluenediamine	Not Available

F-125 PART B

Issue Date: **20/03/2023**Print Date: **15/06/2023** 

#### Transport in bulk in accordance with the IGC Code

Product name	Ship Type
diethyltoluenediamine	Not Available

# **SECTION 15 Regulatory information**

# Safety, health and environmental regulations / legislation specific for the substance or mixture

This substance is to be managed using the conditions specified in an applicable Group Standard

HSR002530 Clear HSR002535 Gas HSR002503 Addi HSR002606 Lubr HSR002612 Meta HSR002624 N.O. HSR002638 Phot HSR002644 Poly HSR002647 Read HSR002648 Refin HSR002653 Solv HSR002670 Surfa	imal Nutritional and Animal Care Products Group Standard 2020 seaning Products Subsidiary Hazard Group Standard 2020 ses under Pressure Mixtures Subsidiary Hazard Group Standard 2020 ditives Process Chemicals and Raw Materials Subsidiary Hazard Group Standard 2020 oricants Lubricant Additives Coolants and Anti freeze Agents Subsidiary Hazard Group Standard 2020 stal Industry Products Subsidiary Hazard Group Standard 2020 O.S. Subsidiary Hazard Group Standard 2020 otographic Chemicals Subsidiary Hazard Group Standard 2020		
HSR002535 Gasc HSR002503 Addi HSR002606 Lubr HSR002612 Meta HSR002624 N.O. HSR002638 Phot HSR002644 Poly HSR002647 Read HSR002648 Refin HSR002653 Solv HSR002670 Surfa	ses under Pressure Mixtures Subsidiary Hazard Group Standard 2020 ditives Process Chemicals and Raw Materials Subsidiary Hazard Group Standard 2020 bricants Lubricant Additives Coolants and Anti freeze Agents Subsidiary Hazard Group Standard 2020 stal Industry Products Subsidiary Hazard Group Standard 2020 D.S. Subsidiary Hazard Group Standard 2020		
HSR002503 Addi HSR002606 Lubr HSR002612 Meta HSR002624 N.O. HSR002638 Phot HSR002644 Poly HSR002647 Rea HSR002648 Refii HSR002653 Solv HSR002670 Surfa	ditives Process Chemicals and Raw Materials Subsidiary Hazard Group Standard 2020  bricants Lubricant Additives Coolants and Anti freeze Agents Subsidiary Hazard Group Standard 2020  tal Industry Products Subsidiary Hazard Group Standard 2020  D.S. Subsidiary Hazard Group Standard 2020		
HSR002606 Lubr HSR002612 Meta HSR002624 N.O. HSR002638 Phot HSR002644 Poly HSR002647 Rea HSR002648 Refit HSR002653 Solv HSR002670 Surfa	bricants Lubricant Additives Coolants and Anti freeze Agents Subsidiary Hazard Group Standard 2020  otal Industry Products Subsidiary Hazard Group Standard 2020  O.S. Subsidiary Hazard Group Standard 2020		
HSR002612 Meta HSR002624 N.O. HSR002638 Phot HSR002644 Poly HSR002647 Read HSR002648 Refii HSR002653 Solv HSR002670 Surfa HSR002684 Wate HSR100425 Phan	tal Industry Products Subsidiary Hazard Group Standard 2020  D.S. Subsidiary Hazard Group Standard 2020		
HSR002624 N.O. HSR002638 Phot HSR002644 Poly HSR002647 Read HSR002648 Refin HSR002653 Solv HSR002670 Surfa HSR002684 Wate HSR100425 Phan	D.S. Subsidiary Hazard Group Standard 2020		
HSR002638 Phot HSR002644 Poly HSR002647 Rea HSR002648 Refii HSR002653 Solv HSR002670 Surfa HSR002684 Wate HSR100425 Phat			
HSR002644 Poly HSR002647 Reag HSR002648 Refii HSR002653 Solv HSR002670 Surfi HSR002684 Wate HSR100425 Phan	otographic Chemicals Subsidiary Hazard Group Standard 2020		
HSR002647 Rear HSR002648 Refii HSR002653 Solv HSR002670 Surfi HSR002684 Wate			
HSR002648 Refii HSR002653 Solv HSR002670 Surfi HSR002684 Wate HSR100425 Phan	lymers Subsidiary Hazard Group Standard 2020		
HSR002653 Solv HSR002670 Surfa HSR002684 Wate HSR100425 Phan	agent Kits Group Standard 2020		
HSR002670 Surfa HSR002684 Wate HSR100425 Phan	fining Catalysts Group Standard 2020		
HSR002684 Wate HSR100425 Phan	lvents Subsidiary Hazard Group Standard 2020		
HSR100425 Phan	Surface Coatings and Colourants Subsidiary Hazard Group Standard 2020		
	Water Treatment Chemicals Subsidiary Hazard Group Standard 2020		
HSB003600 Loot	Pharmaceutical Active Ingredients Group Standard 2020		
HSKUU2000 Leat	Leather and Textile Products Subsidiary Hazard Group Standard 2020		
HSR002544 Con:	onstruction Products Subsidiary Hazard Group Standard 2020		
HSR002549 Corr	rrosion Inhibitors Subsidiary Hazard Group Standard 2020		
HSR002552 Cosi	smetic Products Group Standard 2020		
HSR002558 Dent	ntal Products Subsidiary Hazard Group Standard 2020		
HSR002565 Emb	abalming Products Subsidiary Hazard Group Standard 2020		
HSR002571 Ferti	Fertilisers Subsidiary Hazard Group Standard 2020		
HSR002573 Fire	e Fighting Chemicals Group Standard 2021		
HSR002578 Food	Food Additives and Fragrance Materials Subsidiary Hazard Group Standard 2020		
HSR002585 Fuel	el Additives Subsidiary Hazard Group Standard 2020		
HSR002596 Labo	Laboratory Chemicals and Reagent Kits Group Standard 2020		
HSR100757 Vete	Veterinary Medicines Limited Pack Size Finished Dose Group Standard 2020		
HSR100758 Vete	terinary Medicines Non dispersive Closed System Application Group Standard 2020		
HSR100759 Vete			
HSR100592 Agric	terinary Medicines Non dispersive Open System Application Group Standard 2020		
HSR100756 Activ	terinary Medicines Non dispersive Open System Application Group Standard 2020 ricultural Compounds Special Circumstances Group Standard 2020		

Please refer to Section 8 of the SDS for any applicable tolerable exposure limit or Section 12 for environmental exposure limit.

### diethyltoluenediamine is found on the following regulatory lists

Chemical Footprint Project - Chemicals of High Concern List New Zealand Hazardous Substances and New Organisms (HSNO) Act - Classification of Chemicals New Zealand Hazardous Substances and New Organisms (HSNO) Act - Classification of Chemicals - Classification Data
New Zealand Inventory of Chemicals (NZIoC)

#### **Hazardous Substance Location**

Subject to the Health and Safety at Work (Hazardous Substances) Regulations 2017.

Hazard Class	Quantities
Not Applicable	Not Applicable

# Certified Handler

Subject to Part 4 of the Health and Safety at Work (Hazardous Substances) Regulations 2017.

Class of substance	Quantities
Not Applicable	Not Applicable

Refer Group Standards for further information

# Maximum quantities of certain hazardous substances permitted on passenger service vehicles

Subject to Regulation 13.14 of the Health and Safety at Work (Hazardous Substances) Regulations 2017.

Chemwatch: **5246-49**Version No: **8.1** 

F-125 PART B

Issue Date: **20/03/2023**Print Date: **15/06/2023** 

Hazard Class	Gas (aggregate water capacity in mL)	Liquid (L)	Solid (kg)	Maximum quantity per package for each classification
Not Applicable	Not Applicable	Not Applicable	Not Applicable	Not Applicable

#### **Tracking Requirements**

Not Applicable

#### **National Inventory Status**

National Inventory	Status		
Australia - AIIC / Australia Non-Industrial Use	Yes		
Canada - DSL	Yes		
Canada - NDSL	No (diethyltoluenediamine)		
China - IECSC	Yes		
Europe - EINEC / ELINCS / NLP	Yes		
Japan - ENCS	No (diethyltoluenediamine)		
Korea - KECI	Yes		
New Zealand - NZIoC	Yes		
Philippines - PICCS	Yes		
USA - TSCA	Yes		
Taiwan - TCSI	Yes		
Mexico - INSQ	Yes		
Vietnam - NCI	Yes		
Russia - FBEPH	Yes		
Legend:	Yes = All CAS declared ingredients are on the inventory No = One or more of the CAS listed ingredients are not on the inventory. These ingredients may be exempt or will require registration.		

#### **SECTION 16 Other information**

Revision Date	20/03/2023
Initial Date	10/03/2017

#### **SDS Version Summary**

Version	Date of Update	Sections Updated
7.1	10/12/2021	Classification change due to full database hazard calculation/update.
8.1	20/03/2023	Hazards identification - Classification, Identification of the substance / mixture and of the company / undertaking - Supplier Information, Identification of the substance / mixture and of the company / undertaking - Synonyms, Name

#### Other information

Classification of the preparation and its individual components has drawn on official and authoritative sources as well as independent review by the Chemwatch Classification committee using available literature references.

The SDS is a Hazard Communication tool and should be used to assist in the Risk Assessment. Many factors determine whether the reported Hazards are Risks in the workplace or other settings. Risks may be determined by reference to Exposures Scenarios. Scale of use, frequency of use and current or available engineering controls must be considered.

#### **Definitions and abbreviations**

PC - TWA: Permissible Concentration-Time Weighted Average

PC - STEL: Permissible Concentration-Short Term Exposure Limit

IARC: International Agency for Research on Cancer

ACGIH: American Conference of Governmental Industrial Hygienists

STEL: Short Term Exposure Limit

TEEL: Temporary Emergency Exposure Limit.

IDLH: Immediately Dangerous to Life or Health Concentrations

ES: Exposure Standard

OSF: Odour Safety Factor

NOAEL :No Observed Adverse Effect Level

LOAEL: Lowest Observed Adverse Effect Level

TLV: Threshold Limit Value LOD: Limit Of Detection

OTV: Odour Threshold Value

BCF: BioConcentration Factors

BEI: Biological Exposure Index

AIIC: Australian Inventory of Industrial Chemicals

DSL: Domestic Substances List

NDSL: Non-Domestic Substances List

IECSC: Inventory of Existing Chemical Substance in China

EINECS: European INventory of Existing Commercial chemical Substances

ELINCS: European List of Notified Chemical Substances

NLP: No-Longer Polymers

ENCS: Existing and New Chemical Substances Inventory

KECI: Korea Existing Chemicals Inventory NZIoC: New Zealand Inventory of Chemicals

PICCS: Philippine Inventory of Chemicals and Chemical Substances

TSCA: Toxic Substances Control Act

Chemwatch: 5246-49 Page 10 of 10 Version No: 8.1

F-125 PART B

Issue Date: 20/03/2023 Print Date: 15/06/2023

TCSI: Taiwan Chemical Substance Inventory INSQ: Inventario Nacional de Sustancias Químicas

NCI: National Chemical Inventory FBEPH: Russian Register of Potentially Hazardous Chemical and Biological Substances

This document is copyright.

Apart from any fair dealing for the purposes of private study, research, review or criticism, as permitted under the Copyright Act, no part may be reproduced by any process without written permission from CHEMWATCH.

TEL (+61 3) 9572 4700.