

F-180 PART A BARNES PRODUCTS PTY LTD

Chemwatch: **72-7963** Version No: **8.1**

Safety Data Sheet according to the Health and Safety at Work (Hazardous Substances) Regulations 2017

Chemwatch Hazard Alert Code: 2

Issue Date: **20/03/2023** Print Date: **15/06/2023** S.GHS.NZL.EN.E

SECTION 1 Identification of the substance / mixture and of the company / undertaking

Product Identifier

Product name	F-180 PART A
Chemical Name	Not Applicable
Synonyms	F-180 REV 1 PART A
Chemical formula	Not Applicable
Other means of identification	Not Available

Relevant identified uses of the substance or mixture and uses advised against

Relevant identified uses Polyurethane resin.

Details of the manufacturer or supplier of the safety data sheet

Registered company name	BARNES PRODUCTS PTY LTD			
Address	5 GREENHILLS AVE MOOREBANK NSW 2170 Australia			
Telephone	rnes Australia +612 9793 7555 Mon-Fri 8am-4:30pm			
Fax	Barnes Australia +612 9793 7091			
Website	www.barnesnz.co.nz			
Email	sales@barnes.com.au			

Emergency telephone number

Association / Organisation	New Zealand Poisons Information Centre		
Emergency telephone numbers	nes NZ +649 9731 816 - Monday-Thursday 9am-5pm Friday 9am-4.30pm		
Other emergency telephone numbers	New Zealand Poisons Information Centre 0800 764 766 After Hours		

SECTION 2 Hazards identification

Classification of the substance or mixture

Classification ^[1]	Skin Corrosion/Irritation Category 2, Sensitisation (Skin) Category 1, Serious Eye Damage/Eye Irritation Category 2, Sensitisation (Respiratory Category 1, Specific Target Organ Toxicity - Single Exposure (Respiratory Tract Irritation) Category 3, Carcinogenicity Category 2				
Legend:	1. Classified by Chemwatch; 2. Classification drawn from CCID EPA NZ; 3. Classification drawn from Regulation (EU) No 1272/2008 - Annex VI				
Determined by Chemwatch using GHS/HSNO criteria	6.3A, 6.4A, 6.5A (respiratory), 6.5B (contact), 6.7B, 6.1E (respiratory tract irritant)				

Label elements

Hazard pictogram(s)





Signal word

Hazard statement(s)

Hazaru Statement(S)	
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H319	Causes serious eye irritation.
H334	May cause allergy or asthma symptoms or breathing difficulties if inhaled.
H335	May cause respiratory irritation.
H351	Suspected of causing cancer.

Page 2 of 12

F-180 PART A

Issue Date: 20/03/2023 Print Date: 15/06/2023

Precautionary statement(s) Prevention

P201	Obtain special instructions before use.			
P261	Avoid breathing mist/vapours/spray.			
P271	Use only outdoors or in a well-ventilated area.			
P280	ar protective gloves, protective clothing, eye protection and face protection.			
P284	[In case of inadequate ventilation] wear respiratory protection.			
P264	Wash all exposed external body areas thoroughly after handling.			
P272	Contaminated work clothing should not be allowed out of the workplace.			

Precautionary statement(s) Response

P304+P340	IF INHALED: Remove person to fresh air and keep comfortable for breathing.				
P308+P313	F exposed or concerned: Get medical advice/ attention.				
P342+P311	If experiencing respiratory symptoms: Call a POISON CENTER/doctor/physician/first aider.				
P302+P352	ON SKIN: Wash with plenty of water.				
P305+P351+P338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.				
P312	Call a POISON CENTER/doctor/physician/first aider/if you feel unwell.				
P333+P313	If skin irritation or rash occurs: Get medical advice/attention.				

Precautionary statement(s) Storage

P405	Store locked up.	
P403+P233	Store in a well-ventilated place. Keep container tightly closed.	

Precautionary statement(s) Disposal

P501 Dispose of contents/container to authorised hazardous or special waste collection point in accordance with any local regulation.

SECTION 3 Composition / information on ingredients

Substances

See section below for composition of Mixtures

Mixtures

CAS No	%[weight]	veight] Name			
9057-91-4	10-20	toluene-2.6-diisocyanate, propoxylated			
68515-49-1	5-10	di-C9-11-alkyl phthalate. C10-rich			
78-40-0	<5 <u>triethyl phosphate</u>				
Not Available	balance Ingredients determined not to be hazardous				
Legend:	Classified by Chemwatch; 2. Classification drawn from CCID EPA NZ; 3. Classification drawn from Regulation (EU) No 1272/2008 - Annex VI; Classification drawn from C&L * EU IOELVs available				

SECTION 4 First aid measures

Description of first aid measures

Description of first ald measur	50				
Eye Contact If this product comes in contact with the eyes: Wash out immediately with fresh running water. Ensure complete irrigation of the eye by keeping eyelids apart and away from eye and moving the eyelids by occasion and lower lids. Seek medical attention without delay; if pain persists or recurs seek medical attention. Removal of contact lenses after an eye injury should only be undertaken by skilled personnel.					
Skin Contact	If skin contact occurs: Immediately remove all contaminated clothing, including footwear. Flush skin and hair with running water (and soap if available). Seek medical attention in event of irritation.				
Inhalation	 If fumes or combustion products are inhaled remove from contaminated area. Lay patient down. Keep warm and rested. Prostheses such as false teeth, which may block airway, should be removed, where possible, prior to initiating first aid procedures. Apply artificial respiration if not breathing, preferably with a demand valve resuscitator, bag-valve mask device, or pocket mask as trained. Perform CPR if necessary. Transport to hospital, or doctor, without delay. 				
Ingestion	 If swallowed do NOT induce vomiting. If vomiting occurs, lean patient forward or place on left side (head-down position, if possible) to maintain open airway and prevent aspiration. Observe the patient carefully. Never give liquid to a person showing signs of being sleepy or with reduced awareness; i.e. becoming unconscious. Give water to rinse out mouth, then provide liquid slowly and as much as casualty can comfortably drink. Seek medical advice. 				

Indication of any immediate medical attention and special treatment needed

For sub-chronic and chronic exposures to isocyanates:

- This material may be a potent pulmonary sensitiser which causes bronchospasm even in patients without prior airway hyperreactivity.
- ▶ Clinical symptoms of exposure involve mucosal irritation of respiratory and gastrointestinal tracts.

Page 3 of 12

F-180 PART A

Issue Date: 20/03/2023 Print Date: 15/06/2023

- ▶ Conjunctival irritation, skin inflammation (erythema, pain vesiculation) and gastrointestinal disturbances occur soon after exposure.
- Pulmonary symptoms include cough, burning, substernal pain and dyspnoea.
- Some cross-sensitivity occurs between different isocyanates.
- Noncardiogenic pulmonary oedema and bronchospasm are the most serious consequences of exposure. Markedly symptomatic patients should receive oxygen, ventilatory support and an intravenous line
- Treatment for asthma includes inhaled sympathomimetics (epinephrine [adrenalin], terbutaline) and steroids.
- Activated charcoal (1 g/kg) and a cathartic (sorbitol, magnesium citrate) may be useful for ingestion.
- Mydriatics, systemic analgesics and topical antibiotics (Sulamyd) may be used for corneal abrasions.
- There is no effective therapy for sensitised workers.

[Ellenhorn and Barceloux; Medical Toxicology]

NOTE: Isocyanates cause airway restriction in naive individuals with the degree of response dependant on the concentration and duration of exposure. They induce smooth muscle contraction which leads to bronchoconstrictive episodes. Acute changes in lung function, such as decreased FEV1, may not represent sensitivity

[Karol & Jin, Frontiers in Molecular Toxicology, pp 56-61, 1992]

Personnel who work with isocyanates, isocyanate prepolymers or polyisocyanates should have a pre-placement medical examination and periodic examinations thereafter, including a pulmonary function test. Anyone with a medical history of chronic respiratory disease, asthmatic or bronchial attacks, indications of allergic responses, recurrent eczema or sensitisation conditions of the skin should not handle or work with isocyanates. Anyone who develops chronic respiratory distress when working with isocyanates should be removed from exposure and examined by a physician. Further exposure must be avoided if a sensitivity to isocyanates or polyisocyanates has developed.

Toluene diisocyanate is a known pulmonary sensitiser. Annual medical surveillance should be conducted including pulmonary history, examination of the heart and lungs, 14 x 17 inch (35 x 47 cm) x-ray and pulmonary function testing (FCV, FEV1).

In normal commercial preparations of toluene diisocyanate, the 2,4-isomer dominates in the ratio 4:1. However it is also hydrolysed, in air , more rapidly than the 2,6-isomer. Airway sensitivities may result from the appearance of immunoglobulins in the blood. Frequent inability to detect antibodies to TDI in clinical cases may result from the routine use of diagnostic antigens containing predominantly 2,4-TDI, whereas individuals may have been exposed to atmospheres in which 2,6-TDI was the predominant isomer. [Karol & Jin, Frontiers of Molecular Toxicology, pp 55-61, 1992]

SECTION 5 Firefighting measures

Extinguishing media

- Small quantities of water in contact with hot liquid may react violently with generation of a large volume of rapidly expanding hot sticky semi-solid foam.
- Presents additional hazard when fire fighting in a confined space
- Cooling with flooding quantities of water reduces this risk
- Water spray or fog may cause frothing and should be used in large quantities.
- Foam.
- Dry chemical powder.
- BCF (where regulations permit).
- Carbon dioxide.
- Water spray or fog Large fires only.

Special hazards arising from the substrate or mixture

Fire Incompatibility

▶ Avoid contamination with oxidising agents i.e. nitrates, oxidising acids, chlorine bleaches, pool chlorine etc. as ignition may result

Advice for firefighters

Fire Fighting

- Alert Fire Brigade and tell them location and nature of hazard.
- Wear full body protective clothing with breathing apparatus.
- ▶ Prevent, by any means available, spillage from entering drains or water course.
- Use water delivered as a fine spray to control fire and cool adjacent area
- Avoid spraying water onto liquid pools
 - DO NOT approach containers suspected to be hot.
 - Cool fire exposed containers with water spray from a protected location.

- Moderate fire hazard when exposed to heat or flame.
- When heated to high temperatures decomposes rapidly generating vapour which pressures and may then rupture containers with release of flammable and highly toxic isocyanate vapour.
- Burns with acrid black smoke and poisonous fumes.
- Due to reaction with water producing CO2-gas, a hazardous build-up of pressure could result if contaminated containers are re-sealed.
- Combustion yields traces of highly toxic hydrogen cyanide HCN, plus toxic nitrogen oxides NOx and carbon monoxide.

Fire/Explosion Hazard Combustion products include:

carbon dioxide (CO2)

and minor amounts of

hydrogen cyanide

nitrogen oxides (NOx)

phosphorus oxides (POx)

other pyrolysis products typical of burning organic material.

SECTION 6 Accidental release measures

Personal precautions, protective equipment and emergency procedures

See section 8

Environmental precautions

See section 12

Methods and material for containment and cleaning up

Environmental hazard - contain spillage.

- Remove all ignition sources.
- Clean up all spills immediately.

Minor Spills

- Avoid breathing vapours and contact with skin and eyes
- Control personal contact with the substance, by using protective equipment.
- Contain and absorb spill with sand, earth, inert material or vermiculite
- Wipe up.
- Place in a suitable, labelled container for waste disposal.

Page **4** of **12**

F-180 PART A

Issue Date: 20/03/2023 Print Date: 15/06/2023

Major Spills

Environmental hazard - contain spillage.

Moderate hazard.

- Clear area of personnel and move upwind.
- Alert Fire Brigade and tell them location and nature of hazard.
- Wear breathing apparatus plus protective gloves.
- Prevent, by any means available, spillage from entering drains or water course.
- ▶ No smoking, naked lights or ignition sources.
- Increase ventilation.

Personal Protective Equipment advice is contained in Section 8 of the SDS.

SECTION 7 Handling and storage

Precautions for safe handling

- DO NOT allow clothing wet with material to stay in contact with skin
- Overheating of ethoxylates/ alkoxylates in air should be avoided. When some ethoxylates are heated vigorously in the presence of air or oxygen, at temperatures exceeding 160 C, they may undergo exothermic oxidative degeneration resulting in self-heating and autoignition.
- Nitrogen blanketing will minimise the potential for ethoxylate oxidation. Prolonged storage in the presence of air or oxygen may cause product degradation. Oxidation is not expected when stored under a nitrogen atmosphere. Inert gas blanket and breathing system needed to maintain color stability. Use dry inert gas having at least -40 C dew point.
- Safe handling Avoid all personal contact, including inhalation.
 - Wear protective clothing when risk of exposure occurs.
 - ▶ Use in a well-ventilated area.
 - Prevent concentration in hollows and sumps.
 - ▶ DO NOT enter confined spaces until atmosphere has been checked.
 - Avoid smoking, naked lights or ignition sources.
 - Avoid contact with incompatible materials.
- Other information
- ► Store in original containers.
- ► Keep containers securely sealed.
- No smoking, naked lights or ignition sources.
- ation Store in a cool, dry, well-ventilated area.
 - Store away from incompatible materials and foodstuff containers.
 - Protect containers against physical damage and check regularly for leaks.
 - ▶ Observe manufacturer's storage and handling recommendations contained within this SDS.

Conditions for safe storage, including any incompatibilities

Suitable container

- Packaging as recommended by manufacturer.
- ► Check that containers are clearly labelled and free from leaks
- Storage incompatibility

Avoid reaction with oxidising agents strong acids

SECTION 8 Exposure controls / personal protection

Control parameters

Occupational Exposure Limits (OEL)

INGREDIENT DATA

Source	Ingredient	Material name	TWA	STEL	Peak	Notes
New Zealand Workplace Exposure Standards (WES)	toluene- 2,6-diisocyanate, propoxylated	Isocyanates, all, (as -NCO)	0.02 mg/m3	0.07 mg/m3	Not Available	(dsen) - Dermal sensitiser (rsen) - Respiratory sensitiser (ifv) - The Inhalable Fraction and Vapour (ifv) notation is used when a material exerts sufficient vapour pressure such that it may be present in both particle and vapour phases, with each contributing to a significant portion of exposure

Emergency Limits

Ingredient	TEEL-1	TEEL-2	TEEL-3
triethyl phosphate	23 mg/m3	250 mg/m3	320 mg/m3

Ingredient	Original IDLH	Revised IDLH
toluene-2,6-diisocyanate, propoxylated	Not Available	Not Available
di-C9-11-alkyl phthalate, C10-rich	Not Available	Not Available
triethyl phosphate	Not Available	Not Available

Occupational Exposure Banding

Ingredient	Occupational Exposure Band Rating	Occupational Exposure Band Limit
triethyl phosphate	Е	≤ 0.1 ppm
Notes:	Occupational exposure banding is a process of assigning chemicals into specific categories or bands based on a chemical's potency and the adverse health outcomes associated with exposure. The output of this process is an occupational exposure band (OEB), which corresponds to a range of exposure concentrations that are expected to protect worker health.	

Exposure controls

Appropriate engineering controls

- ▶ All processes in which isocyanates are used should be enclosed wherever possible.
- Total enclosure, accompanied by good general ventilation, should be used to keep atmospheric concentrations below the relevant exposure standards.

Page **5** of **12**

Issue Date: **20/03/2023**Print Date: **15/06/2023**

If total enclosure of the process is not feasible, local exhaust ventilation may be necessary. Local exhaust ventilation is essential where lower molecular weight isocyanates (such as TDI or HDI) is used or where isocyanate or polyurethane is sprayed.

Where other isocyanates or pre-polymers are used and aerosol formation cannot occur, local exhaust ventilation may not be necessary if the atmospheric concentration can be kept below the relevant exposure standards.

Where local exhaust ventilation is installed, exhaust vapours should not be vented to the exterior in such a manner as to create a hazard.

Engineering controls are used to remove a hazard or place a barrier between the worker and the hazard. Well-designed engineering controls can be highly effective in protecting workers and will typically be independent of worker interactions to provide this high level of protection. The basic types of engineering controls are:

Process controls which involve changing the way a job activity or process is done to reduce the risk.

Enclosure and/or isolation of emission source which keeps a selected hazard "physically" away from the worker and ventilation that strategically "adds" and "removes" air in the work environment. Ventilation can remove or dilute an air contaminant if designed properly. The design of a ventilation system must match the particular process and chemical or contaminant in use.

Employers may need to use multiple types of controls to prevent employee overexposure.

Individual protection measures, such as personal protective equipment









protective equipmen

- Safety glasses with side shields.
- ► Chemical goggles. [AS/NZS 1337.1, EN166 or national equivalent]

Eye and face protection

Contact lenses may pose a special hazard; soft contact lenses may absorb and concentrate irritants. A written policy document, describing the wearing of lenses or restrictions on use, should be created for each workplace or task. This should include a review of lens absorption and adsorption for the class of chemicals in use and an account of injury experience. Medical and first-aid personnel should be trained in their removal and suitable equipment should be readily available. In the event of chemical exposure, begin eye irrigation immediately and remove contact lens as soon as practicable.

Skin protection

See Hand protection below

NOTE:

- The material may produce skin sensitisation in predisposed individuals. Care must be taken, when removing gloves and other protective equipment, to avoid all possible skin contact.
- Contaminated leather items, such as shoes, belts and watch-bands should be removed and destroyed.

Hands/feet protection

The selection of suitable gloves does not only depend on the material, but also on further marks of quality which vary from manufacturer to manufacturer. Where the chemical is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

The exact break through time for substances has to be obtained from the manufacturer of the protective gloves and has to be observed when making a final choice.

Personal hygiene is a key element of effective hand care. Gloves must only be worn on clean hands. After using gloves, hands should be washed and dried thoroughly. Application of a non-perfumed moisturiser is recommended.

- ▶ DO NOT use skin cream unless necessary and then use only minimum amount
- Isocyanate vapour may be absorbed into skin cream and this increases hazard.

Body protection

See Other protection below

All employees working with isocyanates must be informed of the hazards from exposure to the contaminant and the precautions necessary to prevent damage to their health. They should be made aware of the need to carry out their work so that as little contamination as possible is produced, and of the importance of the proper use of all safeguards against exposure to themselves and their fellow workers. Adequate training, both in the proper execution of the task and in the use of all associated engineering controls, as well as of any personal protective equipment, is essential.

Other protection

Employees exposed to contamination hazards should be educated in the need for, and proper use of, facilities, clothing and equipment and thereby maintain a high standard of personal cleanliness. Special attention should be given to ensuring that all personnel understand instructions, especially newly recruited employees and those with local-language difficulties, where they are known.

- Overalls.
- P.V.C apron.
- ▶ Barrier cream.
- Skin cleansing cream.
- Eye wash unit.

Respiratory protection

Type A-P Filter of sufficient capacity. (AS/NZS 1716 & 1715, EN 143:2000 & 149:2001, ANSI Z88 or national equivalent)

Where the concentration of gas/particulates in the breathing zone, approaches or exceeds the "Exposure Standard" (or ES), respiratory protection is required. Degree of protection varies with both face-piece and Class of filter; the nature of protection varies with Type of filter.

Required Minimum Protection Factor	Half-Face Respirator	Full-Face Respirator	Powered Air Respirator
up to 10 x ES	A-AUS P2	-	A-PAPR-AUS / Class 1 P2
up to 50 x ES	-	A-AUS / Class 1 P2	-
up to 100 x ES	-	A-2 P2	A-PAPR-2 P2 ^

^ - Full-face

A(All classes) = Organic vapours, B AUS or B1 = Acid gasses, B2 = Acid gas or hydrogen cyanide(HCN), B3 = Acid gas or hydrogen cyanide(HCN), E = Sulfur dioxide(SO2), G = Agricultural chemicals, K = Ammonia(NH3), Hg = Mercury, NO = Oxides of nitrogen, MB = Methyl bromide, AX = Low boiling point organic compounds(below 65 degC)

- Latridge respirators should never be used for emergency ingress or in areas of unknown vapour concentrations or oxygen content.
- The wearer must be warned to leave the contaminated area immediately on detecting any odours through the respirator. The odour may indicate that the mask is not functioning properly, that the vapour concentration is too high, or that the mask is not properly fitted. Because of these limitations, only restricted use of cartridge respirators is considered appropriate.
- Cartridge performance is affected by humidity. Cartridges should be changed after 2 hr of continuous use unless it is determined that the humidity is less than 75%, in which case, cartridges can be used for 4 hr. Used cartridges should be discarded daily, regardless of the length of time used

For spraying or operations which might generate aerosols:

Full face respirator with supplied air.

- In certain circumstances, personal protection of the individual employee is necessary. Personal protective devices should be regarded as being supplementary to substitution and engineering control and should not be used in preference to them as they do nothing to eliminate the hazard.
- However, in some situations, minimising exposure to isocyanates by enclosure and ventilation is not possible, and occupational exposure standards may be exceeded, particularly during on-site mixing of paints, spray-painting, foaming and maintenance of machine and ventilation systems. In these situations, air-line respirators or self-contained breathing apparatus complying with the appropriate nationals standard must be used.
- Organic vapour respirators with particulate pre- filters and powered, air-purifying respirators are NOT suitable.

Issue Date: 20/03/2023 Print Date: 15/06/2023

- Personal protective equipment must be appropriately selected, individually fitted and workers trained in their correct use and maintenance. Personal protective equipment must be regularly checked and maintained to ensure that the worker is being protected.
- Air- line respirators or self-contained breathing apparatus complying with the appropriate national standard should be used during the clean-up of spills and the repair or clean-up of contaminated equipment and similar situations which cause emergency exposures to hazardous atmospheric concentrations of isocyanate.

SECTION 9 Physical and chemical properties

Information on basic physical and chemical properties

	• •		
Appearance	Viscous pale yellow liquid with mild odour; Reacts slightly with water.		
Physical state	Liquid	Relative density (Water = 1)	1.075 @25C
Odour	Not Available	Partition coefficient n-octanol / water	Not Available
Odour threshold	Not Available	Auto-ignition temperature (°C)	Not Available
pH (as supplied)	Not Available	Decomposition temperature (°C)	Not Available
Melting point / freezing point (°C)	Not Available	Viscosity (cSt)	3956.000 @25C
Initial boiling point and boiling range (°C)	>250	Molecular weight (g/mol)	Not Applicable
Flash point (°C)	>160(PMCC)	Taste	Not Available
Evaporation rate	Not Available	Explosive properties	Not Available
Flammability	Not Applicable	Oxidising properties	Not Available
Upper Explosive Limit (%)	Not Available	Surface Tension (dyn/cm or mN/m)	Not Available
Lower Explosive Limit (%)	Not Available	Volatile Component (%vol)	Not Available
Vapour pressure (kPa)	<0.133 @21C	Gas group	Not Available
Solubility in water	Reacts	pH as a solution (1%)	Not Available
Vapour density (Air = 1)	Not Available	VOC g/L	Not Available

SECTION 10 Stability and reactivity

Reactivity	See section 7
Chemical stability	 Unstable in the presence of incompatible materials. Product is considered stable. Hazardous polymerisation will not occur.
Possibility of hazardous reactions	See section 7
Conditions to avoid	See section 7
Incompatible materials	See section 7
Hazardous decomposition products	See section 5

SECTION 11 Toxicological information

nformation on toxicological effects		
Inhaled	The material can cause respiratory irritation in some persons. The body's response to such irritation can cause further lung damage. The vapour/mist may be highly irritating to the upper respiratory tract and lungs; the response may be severe enough to produce bronchitis and pulmonary oedema. Possible neurological symptoms arising from isocyanate exposure include headache, insomnia, euphoria, ataxia, anxiety neurosis, depression and paranoia. Gastrointestinal disturbances are characterised by nausea and vomiting. Pulmonary sensitisation may produce asthmatic reactions ranging from minor breathing difficulties to severe allergic attacks; this may occur following a single acute exposure or may develop without warning for several hours after exposure. Sensitized people can react to very low doses, and should not be allowed to work in situations allowing exposure to this material. Continued exposure of sensitised persons may lead to possible long term respiratory impairment. Inhalation hazard is increased at higher temperatures.	
Ingestion	Considered an unlikely route of entry in commercial/industrial environments Ingestion may result in nausea, abdominal irritation, pain and vomiting The toxicity of phthalates is not excessive due to slow oral absorption and metabolism. Absorption is affected by fat in the diet. Repeated doses can cause cumulative toxic effects, and symptoms include an enlarged liver which often reverses if exposure is maintained. Carbohydrate metabolism is disrupted, and cholesterol and triglyceride levels in the blood falls. In rats, there is also strong evidence of withering of the testicles. Some phthalates can increase the effects of antibiotics, thiamine (vitamin B1) and sulfonamides.	
Skin Contact	This material can cause inflammation of the skin on contact in some persons. The material may accentuate any pre-existing dermatitis condition Open cuts, abraded or irritated skin should not be exposed to this material Entry into the blood-stream, through, for example, cuts, abrasions or lesions, may produce systemic injury with harmful effects. Examine the skin prior to the use of the material and ensure that any external damage is suitably protected.	
Eye	This material can cause eye irritation and damage in some persons.	
Chronic	Long-term exposure to respiratory irritants may result in airways disease, involving difficulty breathing and related whole-body problems. Skin contact with the material is more likely to cause a sensitisation reaction in some persons compared to the general population. Substance accumulation, in the human body, may occur and may cause some concern following repeated or long-term occupational exposure. Persons with a history of asthma or other respiratory problems or are known to be sensitised, should not be engaged in any work involving the handling of isocyanates.	

Page **7** of **12**

Issue Date: 20/03/2023
Print Date: 15/06/2023

The chemistry of reaction of isocyanates, as evidenced by MDI, in biological milieu is such that in the event of a true exposure of small MDI doses to the mouth, reactions will commence at once with biological macromolecules in the buccal region and will continue along the digestive tract prior to reaching the stomach. Reaction products will be a variety of polyureas and macromolecular conjugates with for example mucus, proteins and cell components.

This is corroborated by the results from an MDI inhalation study. Following an inhalation exposure of rats to radiolabelled MDI, 79% of the dose was excreted in faeces. The faecal excretion in these animals was considered entirely due to ingestion of radioactivity from grooming and ingestion of deposited material from the nasopharangeal region via the mucociliary escalator, i.e. not following systemic absorption. The faecal radioactivity was tentatively identified as mixed molecular weight polyureas derived from MDI.

Animal testing shows that polymeric MDI can damage the nasal cavities and lungs, causing inflammation.and increased cell growth.

E 400 DADT A	TOXICITY	IRRITATION
F-180 PART A	Not Available	Not Available
toluene-2,6-diisocyanate,	TOXICITY	IRRITATION
propoxylated	Not Available	Not Available
	TOXICITY	IRRITATION
di-C9-11-alkyl phthalate, C10-rich	dermal (guinea pig) LD50: 10000 mg/kg ^[2]	Eye (rabbit): 500 mg/24h mild
C 10-rich	Oral (Mouse) LD50; 1500 mg/kg ^[2]	Skin (rabbit): 500 mg/24h mild
	TOXICITY	IRRITATION
	Dermal (rabbit) LD50: >20000 mg/kg ^[1]	Eye : Severe *
triethyl phosphate	Inhalation(Rat) LC50: >8.817 mg/L4h ^[1]	Eye: adverse effect observed (irritating) ^[1]
	Oral (Rat) LD50: 1165 mg/kg ^[2]	Skin : Severe *
		Skin: no adverse effect observed (not irritating) ^[1]
Legend:	1. Value obtained from Europe ECHA Registered Substances - Acute toxicity 2. Value obtained from manufacturer's SDS. Unless otherwise	

The following information refers to contact allergens as a group and may not be specific to this product.

Contact allergies quickly manifest themselves as contact eczema, more rarely as urticaria or Quincke's oedema. The pathogenesis of contact eczema involves a cell-mediated (T lymphocytes) immune reaction of the delayed type. Other allergic skin reactions, e.g. contact urticaria, involve antibody-mediated immune reactions. The significance of the contact allergen is not simply determined by its sensitisation potential: the distribution of the substance and the opportunities for contact with it are equally important. A weakly sensitising substance which is widely distributed can be a more important allergen than one with stronger sensitising potential with which few individuals come into contact. From a clinical point of view, substances are noteworthy if they produce an allergic test reaction in more than 1% of the persons tested.

Asthma-like symptoms may continue for months or even years after exposure to the material ends. This may be due to a non-allergic condition known as reactive airways dysfunction syndrome (RADS) which can occur after exposure to high levels of highly irritating compound. Main criteria for diagnosing RADS include the absence of previous airways disease in a non-atopic individual, with sudden onset of persistent asthma-like symptoms within minutes to hours of a documented exposure to the irritant. Other criteria for diagnosis of RADS include a reversible airflow pattern on lung function tests, moderate to severe bronchial hyperreactivity on methacholine challenge testing, and the lack of minimal lymphocytic inflammation, without eosinophilia. RADS (or asthma) following an irritating inhalation is an infrequent disorder with rates related to the concentration of and duration of exposure to the irritating substance. On the other hand, industrial bronchitis is a disorder that occurs as a result of exposure due to high concentrations of irritating substance (often particles) and is completely reversible after exposure ceases. The disorder is characterized by difficulty breathing, cough and mu

TOLUENE-2,6-DIISOCYANATE, PROPOXYLATED

Allergic reactions involving the respiratory tract are usually due to interactions between IgE antibodies and allergens and occur rapidly. Allergic potential of the allergen and period of exposure often determine the severity of symptoms. Some people may be genetically more prone than others, and exposure to other irritants may aggravate symptoms. Allergy causing activity is due to interactions with proteins.

Attention should be paid to atopic diathesis, characterised by increased susceptibility to nasal inflammation, asthma and eczema.

Exogenous allergic alveolitis is induced essentially by allergen specific immune-complexes of the IgG type; cell-mediated reactions (T

lymphocytes) may be involved. Such allergy is of the delayed type with onset up to four hours following exposure.

No significant acute toxicological data identified in literature search.

Polyethers (such as ethoxylated surfactants and polyethylene glycols) are highly susceptible to being oxidized in the air. They then form complex mixtures of oxidation products.

Animal testing reveals that whole the pure, non-oxidised surfactant is non-sensitizing, many of the oxidation products are sensitisers. The oxidization products also cause irritation.

Isocyanate vapours are irritating to the airways and can cause their inflammation, with wheezing, gasping, severe distress, even loss of consciousness and fluid in the lungs. Nervous system symptoms that may occur include headache, sleep disturbance, euphoria, inco-ordination, anxiety, depression and paranoia.

DI-C9-11-ALKYL PHTHALATE,

High Molecular Weight Phthalate Esters (HMWPEs) Category

The HMWPE group includes chemically similar substances produced from alcohols. These substances have been demonstrated to have few biological effects. They demonstrate minimal acute toxicity, with effect on the liver and kidney at high doses. They also cause reproductive and developmental toxicity, also, liver cancer. They are readily metabolised and excreted primarily via the urine. Repeated doses may cause liver and kidney damage, although the relevance to human health is questionable

The material may produce peroxisome proliferation. Peroxisomes are single, membrane limited organelles in the cytoplasm that are found in the cells of animals, plants, fungi, and protozoa.

The material may be irritating to the eye, with prolonged contact causing inflammation. Repeated or prolonged exposure to irritants may produce conjunctivitis.

The material may cause skin irritation after prolonged or repeated exposure and may produce on contact skin redness, swelling, the production of vesicles, scaling and thickening of the skin.

TRIETHYL PHOSPHATE

For toxicological endpoints, the NOAEL is 1000 mg/kg bw for subacute toxicity, a NOEL of 625 mg/kg bw/day for teratogenicity and about 335 mg/kg bw for fertility effects. On the basis of all data on genotoxicity, a mutagenic effect of TEP is not assumed. The substance is harmful with a narcotic effect and, at high doses, shows certain neurotoxic properties (inhibition of cholinesterase) without indicating delayed neurotoxicity. The substance is not irritant to the skin. Studies on experimental animals showed no irritation properties. The most comprehensive documented, actual study (OECD Guideline 405, GLP) showed moderate irritation in 1 of 3 animals. According to the classification guideline this does not lead to a classification as irritant Triethylphosphate administered orally or i.p. to rodents is eliminated rapidly and comprehensively (90% within 16 hours). The very low acute dermal toxicity indicates a markedly lower adsorption than with oral administration. In a subchronic study (rat; oral, up to 6700 mg/kg bw) retarded weight gain, elevated liver and adrenals weight were observed (a validated NOEL or NOAEL cannot be given, the approx. NOEL based on the available data is about 670 mg/kg bw). A subacute 28-day study performed according actual guidelines after oral

Issue Date: **20/03/2023**Print Date: **15/06/2023**

administration to rats determined a NOEL of 100 mg/kg bw (increased liver metabolism). An increase of liver metabolism is of no toxicological relevance, therefore a NOAEL of 1000 mg/kg bw was derived. After high doses to rats a depressive effect on the central nervous system and slight inhibition of cholineesterases are described. In mice, a NOAEL of 274 mg/kg bw was determined in an oral study (1/5 LD 50 = 274 mg/kg bw for 4 weeks) . In rats a NOEL following inhalatory exposure (5h/d for 12 d) of 366 mg/m3 was determined. Conclusion: low toxicity, no serious damage in oral doses up to 6700 mg/kg bw. The NOAEL in the most relevant tests was 1000 mg/kg bw/day. Reproductive Toxicity In an early study using a small number of animals the litter size was reduced after repeated feeding to both sexes (rat) beginning at 670 mg/kg bw, although no symptoms of poisoning in the parent animals were described for the 670 mg/kg bw dose. The NOEL for effects on the litter size was 335 mg/kg bw/day. Neither testicular weights nor the histological investigation of the testes revealed remarkable findings in this study (max. dose 6700 mg/kg bw/day). A more recent 28-day study with doses up to 1000 mg/kg bw also showed no effect on the testicular weight [Bayer 1992]. A teratogenicity study in rats showed no evidence of a teratogenic potential up to the highest dose of 625 mg/kg bw/day (NOEL developmental toxicity). In the highest dose there was reduction of body weight gain, food intake and feces excretion as a sign of maternal toxicity (NOEL 125 mg/kg bw/day). Genetic Toxicity Aside from several Ames tests with negative results, triethylphosphate induces gene mutations without metabolic activation in S. typhimurium his C117, some bacteria, viruses and a yeast strain. For clarification of the endpoint gene mutation a HPRT test in V79 cell cultures was done. This test revealed a negative result with and without metabolic activation. In an in vitro UDS test on rat hepatocytes triethylphosphate showed no DNA-damaging effect. The results for Drosophilia melanogaster in the limited documented recessive-lethal tests are contradictory, while in vivo studies on the mouse (cytogenetics in the bone marrow, dominant lethal test) were negative.

Based on laboratory and animal testing, exposure to the material may result in irreversible effects and mutations in humans. For alkyl phosphates, their salts and esters:

Acute toxicity: The alkyl phosphates, their salts and esters are relatively non-toxic in single-dose studies. Animal testing showed that the esters do not accumulate in the body.

Irritation: Some of the alkyl phosphates are reported to irritate the eye. Generally, animal testing suggests that the lighter the species, the more likely eye irritation is to occur.

Animal testing showed that some alkyl phosphates were not irritating to the skin, while others were irritating but not sensitizing. Again, the lighter species were more likely to cause irritation.

Reproductive toxicity: Animal testing showed that potassium C9-15 alkyl phosphate did not cause toxicity to the embryo or the foetus, and did not cause birth defects. Heavier species had even higher tolerances in testing with respect to reproductive toxicity.

Potential to cause mutations: So far, tests have not shown this group to cause mutations.

Alkyl esters of phosphoric acid exhibit a low to moderate acute toxicity and metabolised. From studies done on mice, they are not likely to cause gene damage or affect reproduction. However, 2-ethylhexanoic acid produced an effect on newborn rats at high doses to the pregnant female. The material may produce severe irritation to the eye causing pronounced inflammation. Repeated or prolonged exposure to irritants may produce conjunctivitis.

NOTE: Substance has been shown to be mutagenic in at least one assay, or belongs to a family of chemicals producing damage or change to cellular DNA.

The material may produce moderate eye irritation leading to inflammation. Repeated or prolonged exposure to irritants may produce conjunctivitis.

Acute Toxicity	×	Carcinogenicity	✓
Skin Irritation/Corrosion	✓	Reproductivity	×
Serious Eye Damage/Irritation	✓	STOT - Single Exposure	✓
Respiratory or Skin sensitisation	✓	STOT - Repeated Exposure	×
Mutagenicity	×	Aspiration Hazard	×

Legend

X - Data either not available or does not fill the criteria for classification

ᢦ – Data available to make classification

SECTION 12 Ecological information

Tox	ic	it۱	ı

	Endpoint	Test Duration (hr)	Species	Value	Source
F-180 PART A	Not Available	Not Available	Not Available	Not Available	Not Available
	Endpoint	Test Duration (hr)	Species	Value	Source
toluene-2,6-diisocyanate, propoxylated	Not Available	Not Available	Not Available	Not Available	Not Available
	Endpoint	Test Duration (hr)	Species	Value	Source
	NOEC(ECx)	504h	Crustacea	>0.03mg/l	1
di-C9-11-alkyl phthalate, C10-rich	LC50	96h	Fish	>0.37mg/l	2
010-11011	EC50	96h	Algae or other aquatic plants	>1.3mg/l	1
	EC50	48h	Crustacea	>0.18mg/l	1
	Endpoint	Test Duration (hr)	Species	Value	Source
triethyl phosphate	BCF	1008h	Fish	0.5-0.8	7
	NOEC(ECx)	Not Available	Crustacea	31.6mg/l	Not Availabl
	EC50	72h	Algae or other aquatic plants	900mg/l	Not Availabl
	LC50	96h	Fish	>100mg/l	Not Availabl

- Bioconcentration Data 8. Vendor Data

Issue Date: 20/03/2023 Print Date: 15/06/2023

Persistence and degradability

Ingredient	Persistence: Water/Soil	Persistence: Air
triethyl phosphate	HIGH	HIGH

Bioaccumulative potential

Ingredient	Bioaccumulation
di-C9-11-alkyl phthalate, C10-rich	HIGH (BCF = 3500)
triethyl phosphate	LOW (BCF = 1.3)

Mobility in soil

Ingredient	Mobility
triethyl phosphate	LOW (KOC = 47.96)

SECTION 13 Disposal considerations

Waste treatment methods

- ▶ Containers may still present a chemical hazard/ danger when empty.
- ▶ Return to supplier for reuse/ recycling if possible

Otherwise:

- If container can not be cleaned sufficiently well to ensure that residuals do not remain or if the container cannot be used to store the same product, then puncture containers, to prevent re-use, and bury at an authorised landfill.
- ▶ Where possible retain label warnings and SDS and observe all notices pertaining to the product.
- DO NOT allow wash water from cleaning or process equipment to enter drains.

Product / Packaging disposal

- It may be necessary to collect all wash water for treatment before disposal.
- In all cases disposal to sewer may be subject to local laws and regulations and these should be considered first.
- ▶ Where in doubt contact the responsible authority.
- ► **DO NOT** recycle spilled material.
- Consult State Land Waste Management Authority for disposal.
- Neutralise spill material carefully and decontaminate empty containers and spill residues with 10% ammonia solution plus detergent or a proprietary decontaminant prior to disposal.
- ▶ DO NOT seal or stopper drums being decontaminated as CO2 gas is generated and may pressurise containers.
- ▶ Puncture containers to prevent re-use.
- Bury or incinerate residues at an approved site.

Ensure that the hazardous substance is disposed in accordance with the Hazardous Substances (Disposal) Notice 2017

Disposal Requirements

Packages that have been in direct contact with the hazardous substance must be only disposed if the hazardous substance was appropriately removed and cleaned out from the package. The package must be disposed according to the manufacturer's directions taking into account the material it is made of. Packages which hazardous content have been appropriately treated and removed may be recycled.

The hazardous substance must only be disposed if it has been treated by a method that changed the characteristics or composition of the substance and it is no longer hazardous. Only dispose to the environment if a tolerable exposure limit has been set for the substance.

Only deposit the hazardous substance into or onto a landfill or sewage facility or incinerator, where the hazardous substance can be handled and treated appropriately.

SECTION 14 Transport information

Labels Required

Marine Pollutant	NO	
HAZCHEM	Not Applicable	

Land transport (UN): NOT REGULATED FOR TRANSPORT OF DANGEROUS GOODS

Air transport (ICAO-IATA / DGR): NOT REGULATED FOR TRANSPORT OF DANGEROUS GOODS

Sea transport (IMDG-Code / GGVSee): NOT REGULATED FOR TRANSPORT OF DANGEROUS GOODS

Transport in bulk according to Annex II of MARPOL and the IBC code

Not Applicable

Transport in bulk in accordance with MARPOL Annex V and the IMSBC Code

Product name	Group
toluene-2,6-diisocyanate, propoxylated	Not Available
di-C9-11-alkyl phthalate, C10-rich	Not Available
triethyl phosphate	Not Available

Transport in bulk in accordance with the IGC Code

Product name	Ship Type
toluene-2,6-diisocyanate, propoxylated	Not Available

Issue Date: 20/03/2023 Print Date: 15/06/2023

Product name	Ship Type
di-C9-11-alkyl phthalate, C10-rich	Not Available
triethyl phosphate	Not Available

SECTION 15 Regulatory information

Safety, health and environmental regulations / legislation specific for the substance or mixture

This substance is to be managed using the conditions specified in an applicable Group Standard

HSR Number	Group Standard	
HSR002521	Animal Nutritional and Animal Care Products Group Standard 2020	
HSR002531	Cleaning Products Carcinogenic Group Standard 2020	
HSR002512	Additives Process Chemicals and Raw Materials Carcinogenic Group Standard 2020	
HSR002607	Lubricants Carcinogenic Group Standard 2020	
HSR002616	Metal Industry Products Carcinogenic Group Standard 2020	
HSR002639	Photographic Chemicals Carcinogenic Group Standard 2020	
HSR002646	Polymers Carcinogenic Group Standard 2020	
HSR002647	Reagent Kits Group Standard 2020	
HSR002648	Refining Catalysts Group Standard 2020	
HSR002655	Solvents Carcinogenic Group Standard 2020	
HSR002679	Surface Coatings and Colourants Carcinogenic Group Standard 2020	
HSR002687	Water Treatment Chemicals Carcinogenic Group Standard 2020	
HSR100425	Pharmaceutical Active Ingredients Group Standard 2020	
HSR002601	Leather and Textile Products Carcinogenic Group Standard 2020	
HSR002551	Corrosion Inhibitors Carcinogenic Group Standard 2020	
HSR002552	Cosmetic Products Group Standard 2020	
HSR002560	Dental Products Carcinogenic Group Standard 2020	
HSR002568	Embalming Products Carcinogenic Group Standard 2020	
HSR002586	Fuel Additives Carcinogenic Group Standard 2020	
HSR002596	Laboratory Chemicals and Reagent Kits Group Standard 2020	
HSR100757	Veterinary Medicines Limited Pack Size Finished Dose Group Standard 2020	
HSR100758	Veterinary Medicines Non dispersive Closed System Application Group Standard 2020	
HSR100759	Veterinary Medicines Non dispersive Open System Application Group Standard 2020	

Please refer to Section 8 of the SDS for any applicable tolerable exposure limit or Section 12 for environmental exposure limit.

toluene-2,6-diisocyanate, propoxylated is found on the following regulatory lists

New Zealand Inventory of Chemicals (NZIoC)

New Zealand Workplace Exposure Standards (WES)

di-C9-11-alkyl phthalate, C10-rich is found on the following regulatory lists

Chemical Footprint Project - Chemicals of High Concern List

New Zealand Inventory of Chemicals (NZIoC)

triethyl phosphate is found on the following regulatory lists

New Zealand Hazardous Substances and New Organisms (HSNO) Act - Classification of Chemicals

New Zealand Inventory of Chemicals (NZIoC)

New Zealand Hazardous Substances and New Organisms (HSNO) Act - Classification of Chemicals - Classification Data

Hazardous Substance Location

Subject to the Health and Safety at Work (Hazardous Substances) Regulations 2017.

Hazard Class	Quantities
Not Applicable	Not Applicable

Certified Handler

Subject to Part 4 of the Health and Safety at Work (Hazardous Substances) Regulations 2017.

Class of substance	Quantities
Not Applicable	Not Applicable

Refer Group Standards for further information

Maximum quantities of certain hazardous substances permitted on passenger service vehicles

Subject to Regulation 13.14 of the Health and Safety at Work (Hazardous Substances) Regulations 2017.

Hazard Class	Gas (aggregate water capacity in mL)	Liquid (L)	Solid (kg)	Maximum quantity per package for each classification
6.5A or 6.5B	120	1	3	

Page 11 of 12 Issue Date: 20/03/2023 Print Date: 15/06/2023

Tracking Requirements

Not Applicable

National Inventory Status

National Inventory	Status			
Australia - AIIC / Australia Non-Industrial Use	Yes			
Canada - DSL	Yes			
Canada - NDSL	No (toluene-2,6-diisocyanate, propoxylated; di-C9-11-alkyl phthalate, C10-rich; triethyl phosphate)			
China - IECSC	Yes			
Europe - EINEC / ELINCS / NLP	No (toluene-2,6-diisocyanate, propoxylated)			
Japan - ENCS	No (toluene-2,6-diisocyanate, propoxylated)			
Korea - KECI	Yes			
New Zealand - NZIoC	Yes			
Philippines - PICCS	Yes			
USA - TSCA	Yes			
Taiwan - TCSI	Yes			
Mexico - INSQ	No (toluene-2,6-diisocyanate, propoxylated; triethyl phosphate)			
Vietnam - NCI	Yes			
Russia - FBEPH	No (toluene-2,6-diisocyanate, propoxylated; di-C9-11-alkyl phthalate, C10-rich)			
Legend:	Yes = All CAS declared ingredients are on the inventory No = One or more of the CAS listed ingredients are not on the inventory. These ingredients may be exempt or will require registration.			

SECTION 16 Other information

Revision Date	20/03/2023
Initial Date	03/03/2017

SDS Version Summary

Version	Date of Update	Sections Updated	
6.1	23/12/2022	Classification review due to GHS Revision change.	
8.1	20/03/2023	Hazards identification - Classification, Composition / information on ingredients - Ingredients, Identification of the substance / mixture and of the company / undertaking - Supplier Information, Identification of the substance / mixture and of the company / undertaking - Synonyms, Name	

Other information

Classification of the preparation and its individual components has drawn on official and authoritative sources as well as independent review by the Chemwatch Classification committee using available literature references.

The SDS is a Hazard Communication tool and should be used to assist in the Risk Assessment. Many factors determine whether the reported Hazards are Risks in the workplace or other settings. Risks may be determined by reference to Exposures Scenarios. Scale of use, frequency of use and current or available engineering controls must be considered.

Definitions and abbreviations

PC - TWA: Permissible Concentration-Time Weighted Average

PC - STEL: Permissible Concentration-Short Term Exposure Limit

IARC: International Agency for Research on Cancer

ACGIH: American Conference of Governmental Industrial Hygienists

STEL: Short Term Exposure Limit

TEEL: Temporary Emergency Exposure Limit₀

IDLH: Immediately Dangerous to Life or Health Concentrations

ES: Exposure Standard

OSF: Odour Safety Factor

NOAEL :No Observed Adverse Effect Level

LOAEL: Lowest Observed Adverse Effect Level

TLV: Threshold Limit Value

LOD: Limit Of Detection

OTV: Odour Threshold Value

BCF: BioConcentration Factors

BEI: Biological Exposure Index

AIIC: Australian Inventory of Industrial Chemicals

DSL: Domestic Substances List

NDSL: Non-Domestic Substances List

IECSC: Inventory of Existing Chemical Substance in China

EINECS: European INventory of Existing Commercial chemical Substances

ELINCS: European List of Notified Chemical Substances

NLP: No-Longer Polymers

ENCS: Existing and New Chemical Substances Inventory

KECI: Korea Existing Chemicals Inventory

NZIoC: New Zealand Inventory of Chemicals

PICCS: Philippine Inventory of Chemicals and Chemical Substances

TSCA: Toxic Substances Control Act

TCSI: Taiwan Chemical Substance Inventory

INSQ: Inventario Nacional de Sustancias Químicas

NCI: National Chemical Inventory

Chemwatch: 72-7963 Page 12 of 12 Version No: 8.1

F-180 PART A

Issue Date: 20/03/2023 Print Date: 15/06/2023

FBEPH: Russian Register of Potentially Hazardous Chemical and Biological Substances

This document is copyright.

Apart from any fair dealing for the purposes of private study, research, review or criticism, as permitted under the Copyright Act, no part may be reproduced by any process without written permission from CHEMWATCH.

TEL (+61 3) 9572 4700.