Pacer Technology

Chemwatch Hazard Alert Code: 2

Chemwatch: 72-79577 Issue Date: 30/12/2020 Version No: 5.1 Print Date: 23/03/2022 S.GHS.AUS.EN

Safety Data Sheet according to WHS Regulations (Hazardous Chemicals) Amendment 2020 and ADG requirements

SECTION 1 Identification of the substance / mixture and of the company / undertaking

Product Identifier

Product name	Pacer Technology ZAP-A-GAP/CA+ 2OZ (72)
Chemical Name	Not Applicable
Synonyms	Product Code: 11730004_PT0
Proper shipping name	AVIATION REGULATED LIQUID, N.O.S. Not subject to this Code (see SP 106) (contains ethyl cyanoacrylate)
Chemical formula	Not Applicable
Other means of identification	Not Available

Relevant identified uses of the substance or mixture and uses advised against

Relevant identified uses Use according to manufacturer's directions.

Details of the supplier of the safety data sheet

Registered company name	Pacer Technology	
Address	3281 E. Guasti Rd., Suite 260 Ontario CA 91761 United States	
Telephone	+1 703 527 3887 Product Stewardship: 909-987-0550	
Fax	Not Available	
Website	http://supergluecorp.com	
Email	info@supergluecorp.com	

Emergency telephone number

Association / Organisation	Pacer Technology	CHEMWATCH EMERGENCY RESPONSE
Emergency telephone numbers	Chemtrec 1-800-424-9300	+61 1800 951 288
Other emergency telephone numbers	Not Available	+61 2 9186 1132

Once connected and if the message is not in your prefered language then please dial 01

SECTION 2 Hazards identification

Classification of the substance or mixture

COMBUSTIBLE LIQUID, regulated for storage purposes only		
Poisons Schedule	Not Applicable	
Classification ^[1]	Serious Eye Damage/Eye Irritation Category 2A, Specific Target Organ Toxicity - Single Exposure (Respiratory Tract Irritation) Category 3, Hazardous to the Aquatic Environment Long-Term Hazard Category 2, Skin Corrosion/Irritation Category 2	
Legend:	1. Classified by Chernwatch; 2. Classification drawn from HCIS; 3. Classification drawn from Regulation (EU) No 1272/2008 - Annex VI	

Label elements

Hazard pictogram(s)	
Signal word	Warning

Hazard statement(s)

H319	Causes serious eye irritation.
H335	May cause respiratory irritation.
H411	Toxic to aquatic life with long lasting effects.
H315	Causes skin irritation.

Precautionary statement(s) Prevention

P271	Use only outdoors or in a well-ventilated area.
P261	Avoid breathing mist/vapours/spray.

P273	Avoid release to the environment.	
P280	Wear protective gloves, protective clothing, eye protection and face protection.	
recautionary statement(s) Res	sponse	
P305+P351+P338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.	
P312	Call a POISON CENTER/doctor/physician/first aider/if you feel unwell.	
P337+P313	If eye irritation persists: Get medical advice/attention.	

Precautionary statement(s) Storage

	-
P405	Store locked up.
P403+P233	Store in a well-ventilated place. Keep container tightly closed.

Precautionary statement(s) Disposal

P501 Dispose of contents/container to authorised hazardous or special waste collection point in accordance with any local regulation.

SECTION 3 Composition / information on ingredients

Substances

See section below for composition of Mixtures

Mixtures

CAS No	%[weight]	Name
7085-85-0	>60	ethyl cyanoacrylate
9011-14-7	10-30	methyl methacrylate homopolymer
123-31-9	<0.1	hydroquinone
Legend:	1. Classified by Chernwatch; 2. Classification drawn from HCIS; 3. Classification drawn from Regulation (EU) No 1272/2008 - Annex VI; 4. Classification drawn from C&L * EU IOELVs available	

SECTION 4 First aid measures

Description of first aid measure	es
Eye Contact	 Eyelid Adhesion Wash thoroughly with water and apply moist pad; maintain in position. DO NOT force separation. Transport to hospital, or doctor without delay. Minor eye contamination should be treated by copious washing with water or 1% sodium carbonate solution. The eye will generally open without further action, typically in one to two days. there should be no residual damage. Adhesive introduced Removal of contact lenses after eye injury should only be undertaken by skilled personnel. Adhesive will attach itself to eye proteins and will disassociate from these over intermittent periods, usually within several hours. This will result in weeping until clearance of the protein complex. It is important to understand that disassociation will normally occur within a matter of hours even with gross contamination.
Skin Contact	Cyanoacrylate adhesives is a very fast setting and strong, they bond human tissues including skin in seconds. Experience shows that accidents involving cyanoacrylates are best handled by passive, non-surgical first aid. Skin Contact: Remove excessive adhesive. Soak in warm water - the adhesive should loosen from the skin in several hours. Dried adhesive does not present a health hazard. Contact with clothes, fabric, rags or tissues may generate heat, and strong irritating odours; skin burns may also ensue. Skin Adhesion: IMMEDATELY immerse affected areas in warm soapy water. DO NOT force bonded surfaces apart. Use a gentle rolling action to peel surfaces apart if possible. It may be necessary to use a blunt edge such as a spatula or spoon handle. Dreve any cure material with warm, soapy water. Seek medical attention without delay. A solvent such as acetone may be used (with carel) to separate bonded skin surfaces. NEVER use solvent near eyes, mouth, cuts, or abrasions. For thermal burns: Decontaminate area around burn. Consider the use of cold packs and topical antibiotics. For first-degree burns (affecting top layer of skin) Hold burned skin under cool (not cold) running water or immerse in cool water until pain subsides. Use compresses if running water is not available. Cover with sterific non-adhesive bandage or clean cloth. Do NOT apply butter or ointments; this may cause infection. Give over-the counter pain relievers if pain increases or swelling, redness, fever occur. For second-degree burns (affecting top two layers of skin) Cool the burn by immerse in coid running water is not available. Use compresses if running water is not available. Do NOT apply butter or ointments; this may cause infection. Give over-the counter pain relievers of skin) Cool the burn by immerse in coid running water is not available. Do NOT apply butter or ointments; this may cause infection. Do NOT apply butter or ointments; this may cause

Protect burn by cover loosely with sterile, nonstick bandage and secure in place with gauze or tape.

	To prevent shock: (unless the person has a head, neck, or leg injury, or it would cause discomfort): Lay the person flat. Elevate feet about 12 inches. Elevate burn area above heart level, if possible.
	Cover the person with coat or blanket.
	Seek medical assistance. For third-degree burns
	Seek immediate medical or emergency assistance.
	In the mean time:
	Protect burn area cover loosely with sterile, nonstick bandage or, for large areas, a sheet or other material that will not leave lint in wound.
	Separate burned toes and fingers with dry, sterile dressings.
	Do not soak burn in water or apply ointments or butter; this may cause infection.
	To prevent shock see above.
	 For an airway burn, do not place pillow under the person's head when the person is lying down. This can close the airway. Have a person with a facial burn sit up.
	 Check pulse and breathing to monitor for shock until emergency help arrives.
Inhalation	 If fumes or combustion products are inhaled remove from contaminated area. Lay patient down. Keep warm and rested. Prostheses such as false teeth, which may block airway, should be removed, where possible, prior to initiating first aid procedures. Apply artificial respiration if not breathing, preferably with a demand valve resuscitator, bag-valve mask device, or pocket mask as trained. Perform CPR if necessary. Transport to hospital, or doctor. If fumes or combustion products are inhaled remove from contaminated area. Lay patient down. Keep warm and rested. Prostheses such as false teeth, which may block airway, should be removed, where possible, prior to initiating first aid procedures. Apply artificial respiration if not breathing, preferably with a demand valve resuscitator, bag-valve mask device, or pocket mask as trained. Prostheses such as false teeth, which may block airway, should be removed, where possible, prior to initiating first aid procedures. Apply artificial respiration if not breathing, preferably with a demand valve resuscitator, bag-valve mask device, or pocket mask as trained. Prostheses such as false teeth, which may block airway, should be removed, where possible, prior to initiating first aid procedures. Apply artificial respiration if not breathing, preferably with a demand valve resuscitator, bag-valve mask device, or pocket mask as trained. Perform CPR if necessary. Transport to hospital, or doctor, without delay.
Ingestion	 Immediately give a glass of water. First aid is not generally required. If in doubt, contact a Poisons Information Centre or a doctor. For material bonded in the mouth seek medical/dental attention. If lips are accidentally stuck together apply lots of warm water and encourage maximum wetting and pressure from saliva inside the mouth. Peal or roll lips apart. Do NOT attempt to pull the lips with direct opposing action. It is almost impossible to swallow cyanoacrylates. The adhesive solidifies and adheres in the mouth. Saliva will lip the adhesion in one or two days.

Indication of any immediate medical attention and special treatment needed

It should never be necessary to use surgical means to separate tissues which become accidentally bonded. The action of physiological fluids or warm soapy water will cause this adhesive to eventually fail. Treat symptomatically.

SECTION 5 Firefighting measures

Extinguishing media

- Foam.
- Dry chemical powder.
 BCF (where regulations permit).
- Carbon dioxide.

Special hazards arising from the substrate or mixture

Fire Incompatibility	Avoid contamination with oxidising agents i.e. nitrates, oxidising acids, chlorine bleaches, pool chlorine etc. as ignition may result
Advice for firefighters	
Fire Fighting	 Alert Fire Brigade and tell them location and nature of hazard. Wear full body protective clothing with breathing apparatus. Prevent, by any means available, spillage from entering drains or water course. Use water delivered as a fine spray to control fire and cool adjacent area.
	 Combustible. Slight fire hazard when exposed to heat or flame.

	 Heating may cause expansion or decomposition leading to violent rupture of containers. On combustion, may emit toxic fumes of carbon monoxide (CO).
Fire/Explosion Hazard	Combustion products include:
	carbon dioxide (CO2)
	aldehydes
	nitrogen oxides (NOx)
	other pyrolysis products typical of burning organic material.
HAZCHEM	2Z

SECTION 6 Accidental release measures

Personal precautions, protective equipment and emergency procedures

See section 8

Environmental precautions

See section 12

Minor Spills	 If cloth has been used to wipe up spills, immediately soak the cloth in water to produce polymerisation and prevent possibility of autoignition. Clean up all spills immediately. Avoid breathing vapours and contact with skin and eyes. Control personal contact with the substance, by using protective equipment. Contain and absorb spill with sand, earth, inert material or vermiculite.
Major Spills	Moderate hazard. Clear area of personnel and move upwind. Alert Fire Brigade and tell them location and nature of hazard. Wear breathing apparatus plus protective gloves.

Personal Protective Equipment advice is contained in Section 8 of the SDS.

SECTION 7 Handling and storage

Precautions for safe handling	
Safe handling	 DO NOT allow clothing wet with material to stay in contact with skin Avoid all personal contact, including inhalation. Wear protective clothing when risk of exposure occurs. Use in a well-ventilated area. Prevent concentration in hollows and sumps.
Other information	 Store in original containers. Keep containers securely sealed. No smoking, naked lights or ignition sources. Store in a cool, dry, well-ventilated area.

Conditions for safe storage, including any incompatibilities

Suitable container	 Metal can or drum Packaging as recommended by manufacturer. Check all containers are clearly labelled and free from leaks.
Storage incompatibility	 Despite the close similarity in structure, the polyacrylates differ greatly in thermal degradation behaviour from the polymethacrylates (PMAs). Crosslinking, yellowing of the polymer, formation of a high proportion of short chain fragments and evolution of the alcohol and carbon dioxide are characteristics of the breakdown of many polyacrylate esters which are not found in the corresponding methacrylate polymers. Furthermore, although some of the latter give large yields of monomer, the monomer yields from the polyacrylates are extremely small, typically about 0.3% of the polymer weight. PMA has been the subject of several studies During degradation, PMA undergoes both crosslinking and chain scission. For cyanoacrylates: Avoid contact with acids, bases, amines. Avoid contact with clothes, fabric, rags (especially cotton and wool) rubber or paper; contact may cause polymerisation. Cyanoacrylate adhesives undergo anionic polymerization in the presence of a weak base, such as water, and are stabilized through the addition of a weak acid. The stabiliser is usually in the form of a weak acidic gas such as SO2, NO, or BF3. Segregate from alcohol, water. Avoid reaction with oxidising agents

SECTION 8 Exposure controls / personal protection

Control parameters

Occupational Exposure Limits (OEL) INGREDIENT DATA

Source	Ingredient	Material name	TWA	STEL	Peak	Notes
Australia Exposure Standards	hydroquinone	Hydroquinone	2 mg/m3	Not Available	Not Available	Not Available

Emergency Limits

Ingredient	TEEL-1	TEEL-2		TEEL-3	
hydroquinone	3 mg/m3	20 mg/m3		120 mg/m3	
Ingredient	Original IDLH		Revised IDLH		
ethyl cyanoacrylate	Not Available			Not Available	
methyl methacrylate homopolymer	Not Available	Not Available		Not Available	
hydroquinone	50 mg/m3	50 mg/m3		Not Available	

Occupational Exposure Banding				
Ingredient	Occupational Exposure Band Rating	Occupational Exposure Band Limit		
ethyl cyanoacrylate	E	≤ 0.1 ppm		
methyl methacrylate homopolymer	E	≤ 0.01 mg/m³		
Notes:	Occupational exposure banding is a process of assigning chemicals into specific categories or bands based on a chemical's potency and the adverse health outcomes associated with exposure. The output of this process is an occupational exposure band (OEB), which corresponds to a range of exposure concentrations that are expected to protect worker health.			

Exposure controls

Appropriate engineering controls

Engineering controls are used to remove a hazard or place a barrier between the worker and the hazard. Well-designed engineering controls can be highly effective in protecting workers and will typically be independent of worker interactions to provide this high level of protection. The basic types of engineering controls are:

	Process controls which involve changing the way a job activity or process is done to reduce the risk. Enclosure and/or isolation of emission source which keeps a selected hazard "physically" away from the worker and ventilation that strategically "adds" and "removes" air in the work environment.
Personal protection	
Eye and face protection	 Safety glasses with side shields. Chemical goggles. Contact lenses may pose a special hazard; soft contact lenses may absorb and concentrate irritants. A written policy document, describing the wearing of lenses or restrictions on use, should be created for each workplace or task.
Skin protection	See Hand protection below
Hands/feet protection	 Wear chemical protective gloves, e.g. PVC. Wear safety footwear or safety gumboots, e.g. Rubber NOTE: The material may produce skin sensitisation in predisposed individuals. Care must be taken, when removing gloves and other protective equipment, to avoid all possible skin contact. Contaminated leather items, such as shoes, belts and watch-bands should be removed and destroyed. The selection of suitable gloves does not only depend on the material, but also on further marks of quality which vary from manufacturer to manufacturer. Where the chemical is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application. The exact break through time for substances has to be obtained from the manufacturer of the protective gloves and has to be observed when making a final choice. Personal hygiene is a key element of effective hand care. Polyethylene gloves
Body protection	See Other protection below
Other protection	 Overalls. P.V.C apron. Barrier cream. Skin cleansing cream.

Recommended material(s)

GLOVE SELECTION INDEX

Glove selection is based on a modified presentation of the:

"Forsberg Clothing Performance Index".

The effect(s) of the following substance(s) are taken into account in the computergenerated selection:

Pacer Technology ZAP-A-GAP/CA+ 2OZ (72)

Material	СРІ
NATURAL RUBBER	A
NATURAL+NEOPRENE	A
NEOPRENE	А
NEOPRENE/NATURAL	A
NITRILE	A
PVC	A

* CPI - Chemwatch Performance Index

A: Best Selection

B: Satisfactory; may degrade after 4 hours continuous immersion C: Poor to Dangerous Choice for other than short term immersion

NOTE: As a series of factors will influence the actual performance of the glove, a final selection must be based on detailed observation. -

* Where the glove is to be used on a short term, casual or infrequent basis, factors such as "feel" or convenience (e.g. disposability), may dictate a choice of gloves which might otherwise be unsuitable following long-term or frequent use. A qualified practitioner should be consulted.

Respiratory protection

Type A-P Filter of sufficient capacity. (AS/NZS 1716 & 1715, EN 143:2000 & 149:2001, ANSI Z88 or national equivalent)

Where the concentration of gas/particulates in the breathing zone, approaches or exceeds the "Exposure Standard" (or ES), respiratory protection is required. Degree of protection varies with both face-piece and Class of filter; the nature of protection varies with Type of filter.

Required Minimum Protection Factor	Half-Face Respirator	Full-Face Respirator	Powered Air Respirator
up to 10 x ES	A-AUS P2	-	A-PAPR-AUS / Class 1 P2
up to 50 x ES	-	A-AUS / Class 1 P2	-
up to 100 x ES	-	A-2 P2	A-PAPR-2 P2 ^

^ - Full-face

A(All classes) = Organic vapours, B AUS or B1 = Acid gasses, B2 = Acid gas or hydrogen cyanide(HCN), B3 = Acid gas or hydrogen cyanide(HCN), E = Sulfur dioxide(SO2), G = Agricultural chemicals, K = Ammonia(NH3), Hg = Mercury, NO = Oxides of nitrogen, MB = Methyl bromide, AX = Low boiling point organic compounds(below 65 degC)

- Cartridge respirators should never be used for emergency ingress or in areas of unknown vapour concentrations or oxygen content.
- ▶ The wearer must be warned to leave the contaminated area immediately on detecting any odours through the respirator. The odour may indicate that the mask is not functioning properly, that the vapour concentration is too high, or that the mask is not properly fitted. Because of these limitations, only restricted use of cartridge respirators is considered appropriate.
- Cartridge performance is affected by humidity. Cartridges should be changed after 2 hr of continuous use unless it is determined that the humidity is less than 75%, in which case, cartridges can be used for 4 hr. Used cartridges should be discarded daily, regardless of the length of time used

SECTION 9 Physical and chemical properties

Information on basic physical and chemical properties

Appearance	Transparent colourless liquid with characteristic odour or irritating odour; does not mix with water.				
Physical state	Liquid Relative density (Water = 1) 1.07				
Odour	Not Available	Partition coefficient n-octanol / water	Not Available		
Odour threshold	Not Available	Auto-ignition temperature (°C)	485		
pH (as supplied)	Not Applicable	Decomposition temperature	Not Available		

Melting point / freezing point (°C)	Not Available	Viscosity (cSt)	74.766-112.15 @25C
Initial boiling point and boiling range (°C)	>149	Molecular weight (g/mol)	Not Applicable
Flash point (°C)	80-93.4 (TCC)	Taste	Not Available
Evaporation rate	Not Available	Explosive properties	Not Available
Flammability	Combustible.	Oxidising properties	Not Available
Upper Explosive Limit (%)	Not Available	Surface Tension (dyn/cm or mN/m)	Not Available
Lower Explosive Limit (%)	Not Available	Volatile Component (%vol)	Not Available
Vapour pressure (kPa)	<0.03	Gas group	Not Available
Solubility in water	Immiscible	pH as a solution (Not Available%)	Not Applicable
Vapour density (Air = 1)	Not Available	VOC g/L	<20

SECTION 10 Stability and reactivity

Reactivity	See section 7
Chemical stability	 Unstable in the presence of incompatible materials. Product is considered stable. Hazardous polymerisation will not occur.
Possibility of hazardous reactions	See section 7
Conditions to avoid	See section 7
Incompatible materials	See section 7
Hazardous decomposition products	See section 5

SECTION 11 Toxicological information

Information on toxicological effects

normation on toxicological er		
Inhaled	The material can cause respiratory irritation in some persons. The body's Inhalation of vapours may cause drowsiness and dizziness. This may be co-ordination, and vertigo. Inhalation of vapours or aerosols (mists, fumes), generated by the materi of the individual. In low humidity, cyanoacrylate vapours are irritating to the respiratory sys and other complications. Prolonged exposure may cause headache, nausea and ultimately loss of	accompanied by sleepiness, reduced alertness, loss of reflexes, lack of ial during the course of normal handling, may be damaging to the health stem and eyes. High concentrations may cause inflammation of the lungs
Ingestion	Although ingestion is not thought to produce harmful effects (as classified of the individual, following ingestion, especially where pre-existing organ Uncured cyanoacrylates are difficult to swallow as saliva cures the surfac considered to be non-hazardous. High molecular weight material; on single acute exposure would be exper Occasionally accumulation of the solid material within the alimentary trac	(e.g. liver, kidney) damage is evident. ce of the adhesive with negligible bonding. The cured material is cted to pass through gastrointestinal tract with little change / absorption.
Skin Contact	This material can cause inflammation of the skin on contact in some pers The material may accentuate any pre-existing dermatitis condition Skin contact is not thought to have harmful health effects (as classified un following entry through wounds, lesions or abrasions. Small n-alkyl cyanoacrylates cause burns and irritation on skin contact. E conditions. Open cuts, abraded or irritated skin should not be exposed to this materia Entry into the blood-stream, through, for example, cuts, abrasions or lesio prior to the use of the material and ensure that any external damage is su	nder EC Directives); the material may still produce health damage Exposure to their vapours can cause irritation, but usually only in dry al ons, may produce systemic injury with harmful effects. Examine the skin
Eye	This material can cause eye irritation and damage in some persons. Exposure to cyanoacrylate vapours can cause discomfort and tears, nasa	al discharge, and blurred vision. The eyelids may be glued shut.
Chronic	Long-term exposure to respiratory irritants may result in airways disease, Skin contact with the material is more likely to cause a sensitisation react There has been some concern that this material can cause cancer or mu Substance accumulation, in the human body, may occur and may cause This material contains a polymer with a functional group considered to be sensitivity) and some species may cause cancer.	tion in some persons compared to the general population. ttations but there is not enough data to make an assessment. some concern following repeated or long-term occupational exposure. e of high concern. Pendant methacrylates are irritating (cause increased
	individuals develop allergic sensitivities. Chronic exposure to cyanides and certain nitriles may result in interference This occurs following metabolic conversion of the cyanide moiety to thioc	
	individuals develop allergic sensitivities. Chronic exposure to cyanides and certain nitriles may result in interference	ce to iodine uptake by thyroid gland and its consequent enlargement.
Pacer Technology ZAP-A- GAP/CA+ 202 (72)	individuals develop allergic sensitivities. Chronic exposure to cyanides and certain nitriles may result in interference This occurs following metabolic conversion of the cyanide moiety to thioc	ce to iodine uptake by thyroid gland and its consequent enlargement. yanate.
	individuals develop allergic sensitivities. Chronic exposure to cyanides and certain nitriles may result in interference. This occurs following metabolic conversion of the cyanide moiety to thioc TOXICITY	ce to iodine uptake by thyroid gland and its consequent enlargement. cyanate.
	individuals develop allergic sensitivities. Chronic exposure to cyanides and certain nitriles may result in interference This occurs following metabolic conversion of the cyanide moiety to thioc TOXICITY Dermal (None) LD50: >2000 mg/kg* ^[2]	ce to iodine uptake by thyroid gland and its consequent enlargement. cyanate.

	Inhalation(Rat) LC50; 5.278 mg/L4h ^[2]		
	Oral (Rat) LD50; 190.8 mg/kg ^[2]		
methyl methacrylate	ΤΟΧΙΟΙΤΥ	IRRITATION	
homopolymer	Not Available	Not Available	
	тохісітү	IRRITATION	
hydroquinone	Dermal (rabbit) LD50: >2000 mg/kg ^[1]	Skin (human): 2	% - mild
	Oral (Rat) LD50; 320 mg/kg ^[2]	Skin (human): 5	% - SEVERE
Legend:	 Value obtained from Europe ECHA Registered Sul specified data extracted from RTECS - Register of To 		ained from manufacturer's SDS. Unless otherwise
	•		
ETHYL CYANOACRYLATE	For methyl cyanoacrylate (MCA) and ethyl cyanoacry Studies show that the key toxicological features of MC cause eye and skin irritation on repeated exposure bu does not cause genetic toxicity but presents similar hu similarities, similar physicochemical properties and to * [AIHAAP]	CA and ECA are as a result of local ad ut inconclusive evidence of skin sensit ealth effect predicted to be due to its s	ization and asthma causing effect. ECA and MCA
METHYL METHACRYLATE HOMOPOLYMER	Polymethyl methacrylate (PMMA) and related cosmet dimethacrylate crosspolymer are polymers that functi Administration (FDA) determination of safety of PMMA as the basis of safety of PMMA and related polymers cosmetics is substantially the same as in medical dev practices of use and concentrations as described in the J Toxicol. No significant acute toxicological data ident	on as film formers and viscosity-increa A use in several medical devices, whi in cosmetics by the Cosmetic Ingredi rices. The Panel concluded that these his safety assessment	asing agents in cosmetics. The Food and Drug ch included human and animal safety data, was used ent Review (CIR) Expert Panel. The PMMA used in
HYDROQUINONE	The following information refers to contact allergens a Contact allergies quickly manifest themselves as com eczema involves a cell-mediated (T lymphocytes) imr involve antibody-mediated immune reactions. The material may cause severe skin irritation after pro production of vesicles, scaling and thickening of the s Animal testing shows that hydroquinone is rapidly and accelerated with alcohols. Hydroquinone distributes r In animals, hydroquinone has moderate oral acute to:	tact eczema, more rarely as urticaria of nune reaction of the delayed type. Oth blonged or repeated exposure and ma ikin. Repeated exposures may produc d extensively absorbed from the gut at apidly and widely among tissues. It is	or Quincke's oedema. The pathogenesis of contact her allergic skin reactions, e.g. contact urticaria, hy produce on contact skin redness, swelling, the he severe ulceration. Ind lung. Absorption via the skin is slow, but may be
ETHYL CYANOACRYLATE & METHYL METHACRYLATE HOMOPOLYMER	Asthma-like symptoms may continue for months or ex known as reactive airways dysfunction syndrome (RA criteria for diagnosing RADS include the absence of p asthma-like symptoms within minutes to hours of a do airflow pattern on lung function tests, moderate to sev lymphocytic inflammation, without eosinophilia.	NDS) which can occur after exposure to previous airways disease in a non-ato pocumented exposure to the irritant. Ot	o high levels of highly irritating compound. Main pic individual, with sudden onset of persistent her criteria for diagnosis of RADS include a reversibl
METHYL METHACRYLATE HOMOPOLYMER & HYDROQUINONE	The substance is classified by IARC as Group 3: NOT classifiable as to its carcinogenicity to humans. Evidence of carcinogenicity may be inadequate or lim	ited in animal testing.	
Acute Toxicity	×	Carcinogenicity	×
Skin Irritation/Corrosion	✓	Reproductivity	×
Serious Eye Damage/Irritation	✓	STOT - Single Exposure	✓
Respiratory or Skin sensitisation	×	STOT - Repeated Exposure	×
Mutagenicity	×	Aspiration Hazard	×

X − Data either not available or does not fill the criteria for classification
→ Data available to make classification

SECTION 12 Ecological information

Toxicity

	Endpoint	Test Duration (hr)	Species	Value	Source
Pacer Technology ZAP-A- GAP/CA+ 2OZ (72)	Not Available	Not Available	Not Available	Not Available	Not Available
	Endpoint	Test Duration (hr)	Species	Value	Source
ethyl cyanoacrylate	Not Available	Not Available	Not Available	Not Available	Not Available
	Endpoint	Test Duration (hr)	Species	Value	Source
methyl methacrylate homopolymer	Not Available	Not Available	Not Available	Not Available	Not Available
	Endpoint	Test Duration (hr)	Species	Value	Source
hydroquinone	NOEC(ECx)	72h	Algae or other aquatic plants	0.002mg/l	2

	LC50	96h	Fish	0.044mg/l	2
	EC50	72h	Algae or other aquatic plants	<0.033mg/l	2
	EC50	48h	Crustacea	0.061mg/l	2
Legend:	Ecotox database		d Substances - Ecotoxicological Information - Aqua rd Assessment Data 6. NITE (Japan) - Bioconcentr		

Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

Do NOT allow product to come in contact with surface waters or to intertidal areas below the mean high water mark. Do not contaminate water when cleaning equipment or disposing of equipment wash-waters.

Wastes resulting from use of the product must be disposed of on site or at approved waste sites.

For high molecular weight synthetic polymers: (according to the Sustainable Futures (SF) program (U.S. EPA 2005b; U.S. EPA 2012c) polymer assessment guidance.)

High MW polymers are expected:

• to have low vapour pressure and are not expected to undergo volatilization .

· to adsorb strongly to soil and sediment

• to be non-biodegradable (not anticipated to be assimilated by microorganisms.- therefore, biodegradation is not expected to be an important removal process. However many exceptions exist

High MW polymers are not expected to undergo removal by other degradative processes under environmental conditions

Substances containing unsaturated carbons are ubiquitous in indoor environments. They result from many sources (see below). Most are reactive with environmental ozone and many produce stable products which are thought to adversely affect human health. The potential for surfaces in an enclosed space to facilitate reactions should be considered. Source of unsaturated substances Unsaturated substances (Reactive Emissions) Major Stable Products produced following reaction with ozone.

DO NOT discharge into sewer or waterways.

Persistence and degradability

Ingredient	Persistence: Water/Soil	Persistence: Air
ethyl cyanoacrylate	LOW	LOW
methyl methacrylate homopolymer	LOW (Half-life = 56 days)	LOW (Half-life = 0.4 days)
hydroquinone	LOW	LOW

Bioaccumulative potential

Ingredient	Bioaccumulation
ethyl cyanoacrylate	LOW (LogKOW = 1.4174)
methyl methacrylate homopolymer	LOW (LogKOW = 1.2751)
hydroquinone	LOW (BCF = 65)

Mobility in soil

Ingredient	Mobility
ethyl cyanoacrylate	LOW (KOC = 6.847)
methyl methacrylate homopolymer	LOW (KOC = 10.14)
hydroquinone	LOW (KOC = 434)

SECTION 13 Disposal considerations

Waste treatment methods

	Containers may still present a chemical hazard/ danger when empty.
	Return to supplier for reuse/ recycling if possible.
	Otherwise:
	If container can not be cleaned sufficiently well to ensure that residuals do not remain or if the container cannot be used to store the same product, then puncture containers, to prevent re-use, and bury at an authorised landfill.
	Where possible retain label warnings and SDS and observe all notices pertaining to the product.
	Legislation addressing waste disposal requirements may differ by country, state and/ or territory. Each user must refer to laws operating in their area. In some areas, certain wastes must be tracked.
	A Hierarchy of Controls seems to be common - the user should investigate:
	▶ Reduction
reduct (Deckering dispess)	▶ Reuse
roduct / Packaging disposal	▶ Recycling
	Disposal (if all else fails)
	This material may be recycled if unused, or if it has not been contaminated so as to make it unsuitable for its intended use.
	DO NOT allow wash water from cleaning or process equipment to enter drains.
	It may be necessary to collect all wash water for treatment before disposal.
	In all cases disposal to sewer may be subject to local laws and regulations and these should be considered first.
	Where in doubt contact the responsible authority.
	Recycle wherever possible or consult manufacturer for recycling options.
	Consult State Land Waste Authority for disposal.
	Bury or incinerate residue at an approved site.
	Recycle containers if possible, or dispose of in an authorised landfill.

SECTION 14 Transport information

Marine Pollutant	
HAZCHEM	2Z

Land transport (ADG): NOT REGULATED FOR TRANSPORT OF DANGEROUS GOODS

Air transport (ICAO-IATA / DGR)

UN number	3334		
UN proper shipping name	Aviation regulated liquid,	n.o.s. * (contains ethyl cyanoacrylate)	
-	ICAO/IATA Class	9	
Transport hazard class(es)	ICAO / IATA Subrisk ERG Code	Not Applicable 9A	
		30	
Packing group	Ш		
Environmental hazard	Environmentally hazardo	bus	
	Special provisions		A27
			AZI
	Cargo Only Packing Instructions		964
	Cargo Only Maximum	Qty / Pack	450L
Special precautions for user	Passenger and Cargo Packing Instructions		964
	Passenger and Cargo Maximum Qty / Pack		450L
	Passenger and Cargo	Limited Quantity Packing Instructions	Y964
	Passenger and Cargo	Limited Maximum Qty / Pack	30 kg G

Sea transport (IMDG-Code / GGVSee): NOT REGULATED FOR TRANSPORT OF DANGEROUS GOODS

Transport in bulk according to Annex II of MARPOL and the IBC code

Not Applicable

Transport in bulk in accordance with MARPOL Annex V and the IMSBC Code

Product name	Group
ethyl cyanoacrylate	Not Available
methyl methacrylate homopolymer	Not Available
hydroquinone	Not Available

Transport in bulk in accordance with the ICG Code

Product name	Ship Type
ethyl cyanoacrylate	Not Available
methyl methacrylate homopolymer	Not Available
hydroquinone	Not Available

SECTION 15 Regulatory information

Safety, health and environmental regulations / legislation specific for the substance or mixture

ethyl cyanoacrylate is found on the following regulatory lists

Australia Hazardous Chemical Information System (HCIS) - Hazardous Chemicals Australia Standard for the Uniform Scheduling of Medicines and Poisons (SUSMP) -Schedule 5

methyl methacrylate homopolymer is found on the following regulatory lists

Australian Inventory of Industrial Chemicals (AIIC)

hydroquinone is found on the following regulatory lists

Australian Inventory of Industrial Chemicals (AIIC)

International Agency for Research on Cancer (IARC) - Agents Classified by the IARC Monographs

Australia Hazardous Chemical Information System (HCIS) - Hazardous Chemicals Australia Standard for the Uniform Scheduling of Medicines and Poisons (SUSMP) -Schedule 2

Australia Standard for the Uniform Scheduling of Medicines and Poisons (SUSMP) - Schedule 4 $\,$

Australia Standard for the Uniform Scheduling of Medicines and Poisons (SUSMP) - Schedule 5

Australia Standard for the Uniform Scheduling of Medicines and Poisons (SUSMP) - Schedule ${\bf 6}$

Australian Inventory of Industrial Chemicals (AIIC)

Chemical Footprint Project - Chemicals of High Concern List

International Agency for Research on Cancer (IARC) - Agents Classified by the IARC Monographs

National Inventory Status

National Inventory	Status		
Australia - AIIC / Australia Non-Industrial Use	Yes		
Canada - DSL	Yes		
Canada - NDSL	No (ethyl cyanoacrylate; methyl methacrylate homopolymer; hydroquinone)		
China - IECSC	Yes		
Europe - EINEC / ELINCS / NLP	No (methyl methacrylate homopolymer)		
Japan - ENCS	No (methyl methacrylate homopolymer)		
Korea - KECI	Yes		
New Zealand - NZIoC	Yes		
Philippines - PICCS	Yes		
USA - TSCA	Yes		
Taiwan - TCSI	Yes		
Mexico - INSQ	Yes		
Vietnam - NCI	Yes		
Russia - FBEPH	Yes		
Legend:	Yes = All CAS declared ingredients are on the inventory No = One or more of the CAS listed ingredients are not on the inventory. These ingredients may be exempt or will require registration.		

SECTION 16 Other information

Revision Date	30/12/2020
Initial Date	05/05/2020

SDS Version Summary

Version	Date of Update	Sections Updated
4.1	07/10/2020	Acute Health (inhaled), Acute Health (skin), Acute Health (swallowed), Appearance, Classification, Engineering Control, Fire Fighter (fire/explosion hazard), First Aid (eye), First Aid (inhaled), First Aid (skin), First Aid (swallowed), Handling Procedure, Ingredients, Instability Condition, Personal Protection (other), Personal Protection (hands/feet), Physical Properties, Spills (major), Storage (storage incompatibility), Synonyms, Name
5.1	30/12/2020	Classification change due to full database hazard calculation/update.

Other information

Classification of the preparation and its individual components has drawn on official and authoritative sources as well as independent review by the Chemwatch Classification committee using available literature references.

The SDS is a Hazard Communication tool and should be used to assist in the Risk Assessment. Many factors determine whether the reported Hazards are Risks in the workplace or other settings. Risks may be determined by reference to Exposures Scenarios. Scale of use, frequency of use and current or available engineering controls must be considered.

Definitions and abbreviations

PC-TWA: Permissible Concentration-Time Weighted Average PC-STEL: Permissible Concentration-Short Term Exposure Limit IARC: International Agency for Research on Cancer ACGIH: American Conference of Governmental Industrial Hygienists STEL: Short Term Exposure Limit TEEL: Temporary Emergency Exposure Limit。 IDLH: Immediately Dangerous to Life or Health Concentrations ES: Exposure Standard OSF: Odour Safety Factor NOAEL :No Observed Adverse Effect Level LOAEL: Lowest Observed Adverse Effect Level TLV: Threshold Limit Value LOD: Limit Of Detection OTV: Odour Threshold Value BCF: BioConcentration Factors **BEI: Biological Exposure Index** AIIC: Australian Inventory of Industrial Chemicals DSL: Domestic Substances List NDSL: Non-Domestic Substances List IECSC: Inventory of Existing Chemical Substance in China EINECS: European INventory of Existing Commercial chemical Substances ELINCS: European List of Notified Chemical Substances NLP: No-Longer Polymers ENCS: Existing and New Chemical Substances Inventory

KECI: Korea Existing Chemicals Inventory NZIoC: New Zealand Inventory of Chemicals PICCS: Philippine Inventory of Chemicals and Chemical Substances TSCA: Toxic Substances Control Act TCSI: Taiwan Chemical Substance Inventory INSQ: Inventario Nacional de Sustancias Químicas NCI: National Chemical Inventory FBEPH: Russian Register of Potentially Hazardous Chemical and Biological Substances

This document is copyright.

Apart from any fair dealing for the purposes of private study, research, review or criticism, as permitted under the Copyright Act, no part may be reproduced by any process without written permission from CHEMWATCH.

TEL (+61 3) 9572 4700.